WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| County | | action / | Section | number | Township number | Range number | |
|---|-----------------------------|------------------------|-------------------------------------|--------|--|--|---------------------|
| | | E 1/4 NW 1/4 NW | | | т 23 s | R / | ₩ |
| 2. Distance and direction from neare | est town or city: 3/4 / | nile West-Hawke | | " PE | TER Neufeld | L | |
| Street address of well location if in a | ity: 10+#2 -B | 15#1 of | R.R. or street: City, state, zip | code: | P.O. BOX 88 Newton Ls | 67114 | |
| 4. Locate with "X" in section below | Mortane Sus | Ch map: | | | 6. Bore hole dia. | | 76 |
| N | | Sewer | | | Well depthft. 7 Cable tool | | <u></u> |
| | ١. ٨ | L' Mwell | | | Hollow rod Jetted | | rse rotary |
| <u> </u> | | ~~ | Ì | | 8. Use: X Domestic P | | , |
| W | | | | | Irrigation A Lawn C | ir conditioning State Oil field water O | ock ther |
| SW SE | | | i | | 9. Casing: Materia | | pelow |
| ! | | \sim | 1 | | Threaded Welded RMP PVC | | in. |
| 1 Mile ——— | | | · | Τ. | Dia in. to ft. dep Dia in. to ft. dep | oth Wall Thickness: in | SB or |
| 5. Type and color of material | | | From | То | 10. Screen: Manufacturer's | name | |
| LOAM | | | 0 | 5 | Type Pur PCO | Dia. 5' | |
| dab h | | nd du chi | 01/ | 10 | Slot/gauze | Length | |
| , . | | | | 10 | ft. | and | |
| - Hight | br. CLAY | | | 17 | Gravel pack? Size ro | | ./day/yr. |
| fine Si | and the | CLAY | 19 | 2/ | 20 ft. below land su | | 9/79 |
| DIRWAL | grey CL | 44 | 21 | 30 | 12. Pumping level below lan | | _ g.p.m. |
| SHNOV | BROWN C | LAV | 30 | 35 | 30 ft. after 2 | hrs. pumping 15 | _ g.p.m. |
| SANA | + clas | Pus | 35 | 42 | Estimated maximum yield — 13. Water sample submitted: | mo | g.p.m. ./day/yr. |
| 04.20 | 2400 (560 | 10 | 42 | | Yes X No | Date | |
| green | grey She | | | | 14. Well head completion: X Pitless adapter | 18 Inches above | grade |
| grey to | Dork Si | to le | 45 | 48 | 15. Well grouted? With: Neat cement | Rentonite | Concrete |
| | | | | - | cepth: From ft. to | ft. | And I |
| | | | | ļ | 16. Nearest source of possib | le contamination: | ouse |
| | | | | | Well disinfected upon compl | | No |
| | | | | | 17. Pump: Manufacturer's name | Not installed | ~ `\ |
| | | | | | Model number #86-3-5 | 70 52 - 1/2 Vo ft. capacity / | olts <u>230</u> |
| | · | 7 | | + | Length of drop pipe | | , |
| | | | | - | Submersible Jet | Turbin Recip | rocating |
| T | (Use a second shee | t if needed) | | | Centrifugal | Other | 1 (0 1 |
| 18. Elevation: 19. Remarks: | | | | | 20. Water well contractor's This well was drilled under | | |
| Topography: | | | | | is true to the best of my kno | wledge and belief. | 25- ∑ \ ∑ |
| Hill | | | | | Business name | LECT | cense No. |
| Slope Upland | | | | | Address Bul R | and list | 3/19/75 |
| Valley | | | | | Signed Authorized re | presentative Date | \$ \\ \frac{1}{2} |
| Forward the white, blue and pink co | pies to the Department of I | Health and Environment | | | | Form W | WC- 5 |