

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		NE 1/4 NE 1/4 NW 1/4	30	T 23 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 5 1/2 miles West of Newton - Hwy 50					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 122 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 48 ft. 2. 98 ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 52 ft. below land surface measured on mo/day/yr 9-12-83			
		Pump test data: Well water was 82 ft. after 2 hours pumping 15 gpm			
		Est. Yield 30+ gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 122 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		<input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped Welded Threaded			
1 Steel 3 RMP (SR)					
<input checked="" type="radio"/> 2 PVC 4 ABS					
Blank casing diameter 5 in. to 102 ft., Dia					
Casing height above land surface 18 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 1025 8 Saw cut Factory 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:					
From 102 ft. to 122 ft., From ft. to ft.					
GRAVEL PACK INTERVALS:					
From 10 ft. to 122 ft., From ft. to ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens *14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
<input checked="" type="radio"/> Sewer lines house 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet? 50 *39'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	loam & dune sand			
5	9	sand fine			
9	29	red brown clay			
29	40	fine sand & thin clay layers			
40	63	med fine sand			
63	78	light grey clay			
78	98	dark grey clay			
98	123	sand - med to coarse - cemented w/ chlorides - "Egus Bed"			
* Existing well - filled-grouted & cemented below grt.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-12-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 175 This Water Well Record was completed on (mo/day/yr) 10-28-83 under the business name of Paul's Inc. by (signature) Paul Bundhart					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					