


WATER WELL RECORD Form WWC-5 KSA 82a-1212					
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		SE 1/4 NE 1/4 SW 1/4	30	T 23 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 mile EAST of Halstead					
2 WATER WELL OWNER: Ken R Koehn RR # 2 Halstead, KS 67056 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 11.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 7.3 ft. 2. 8.9 ft. 3. ft. WELL'S STATIC WATER LEVEL 8.3 ft. below land surface measured on mo/day/yr 10-7-83 Pump test data: Well water was 8.0 ft. after 1 1/2 hours pumping 2.0 gpm Est. Yield 3.0 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to 11.5 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 9.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 1.8 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 2.14 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1.025 8 Saw cut factory 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 9.5 ft. to 11.5 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 1.0 ft. to 1.5 ft. From ft. to ft. From ft. to ft. From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 1.0 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines in house 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? NW How many feet? 40' FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 12 Sandy loam + sandy clay 12 25 red brown clay 25 73 light blue grey clay 73 82 fine sand 82 89 light brown clay 89 115 Sand med fine to coarse - compacted/cemented w/ clonite					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 10-27-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 175 This Water Well Record was completed on (mo/day/yr) 11/23/83 under the business name of Paul's Inc by (signature) Paul Buchland INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					