

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: SEPTOIA Fraction: S.W. 1/4 S.W. 1/4 D.W. 1/4 Section Number: 24 Township Number: T 23 S Range Number: R 1 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: John K. Began RR#, St. Address, Box #: 925 Rangy Creek Dr. City, State, ZIP Code: Newton KS, 67114 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SW section of the bottom-left 4-section block]

4 DEPTH OF COMPLETED WELL: 73 ft. ELEVATION: 6-17-98 ft.

Depth(s) Groundwater Encountered 1. 18 ft. 2. 73 ft. 3. 73 ft.

WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 6-17-98

Pump test data: Well water was 25 ft. after 1 hours pumping 20 gpm

Est. Yield 20 gpm: Well water was 25 ft. after 1 hours pumping 20 gpm

Bore Hole Diameter 1.0 in. to 73 ft., and 73 in. to 73 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 5 in. to 73 ft., Dia 73 in. to 73 ft., Dia 73 in. to 73 ft.

Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 25 ft. to 73 ft., From 73 ft. to 73 ft., From 73 ft. to 73 ft.

GRAVEL PACK INTERVALS: From 73 ft. to 20 ft., From 20 ft. to 20 ft., From 20 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 20 ft. to 20 ft., From 3 ft. to 3 ft., From 3 ft. to 3 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 25 Clay - Silty Brown Clay

25 73 Blue shale, small green shale layers.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-17-98 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 623 This Water Well Record was completed on (mo/day/yr) 7-1-98

under the business name of Chase Drilling by (signature) Alan Chase

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4