			WA	TER WELL RECORD	Form WWC	C-5 KS	A 82a-12	12 ID No. <u>0</u>	042603			
1 LOCATION OF WATER WELL:						Section N	lumber	Township I	Number	Range Number		
County:			SW ½		SW 1/4	18	3	T 23	S	R	1	E
				address of well if loca 1804 W. 4 th St., N		y?						
			darko Develo		vewton							
	Idress, Box #			hineiri				December 4 and	dan dan Di	.i.i£141	/ D	
			rillo, TX 791	05				Board of Agr		ision of vv	ater Reso	ources
LOCATE	WELL'S LOC	ATON WIT	THI.					Application I				
3 AN "X" II	N SECTION B	OX:	- DEPTH OF	COMPLETED WELL	L	25	ft. ELEV	ATION:	1440	0.15 (TC)C)	
1			Depth(s) Grou	ndwater Encountered	1 1	22	ft.	2	ft.	3		ft.
-	NW	- NE		IC WATER LEVEL								
		i	Pu	mp test data: Well v	water was		ft.	after	hours	pumping		gpm
₩ W -	-		E Est. Yield	gpm: Well v	water was		ft.	after	hours	pumping		gpm
ī			Bore Hole Dia	meter 8.25 in.	to	25		ft and	i	n to		ft.
X	sw	- SE	WELL WATER	R TO BE USED AS: stic 3 Feed lot	5 Public wa	iter supply	,	8 Air condit	ioning	1 Injectio	n well	
↓ . I	İ									12 Other (Specify b	elow)
· _	S		1	on 4 Industrial								
			Was a chemic	al/bacteriological sam	nple submitte	d to Depa						was
			submitted					er Well Disinfed				
5 TYPE O	F BLANK CAS	SING USEE):	5 Wrought Iron					INTS: Glue	ed	Clampe	d
1 Ste	eel	3 RM	P (SR)	6 Asbestos-Ce	ment 9 C	Other (spe	cify belov		Wel			
2 PV	′C	4 AB	3	7 Fiberglass					Threa	aded	Flus	h
Blank casin	g diameter	2	in. to	15 ft., Dia		in. to		ft., Dia		in. to		ft.
Casing heig	ht above land	surface	Flushmount	in., weight	0.703	- '-'	lbs./ft.	Wall thickness	or gauge No	,	3CH. 4	0
			ION MATERIAL:			7 PVC		10 As	bestos-cem	ent		
1 Ste	eel	3 Sta	inless steel	5 Fiberglass								
2 Bra			lvanized steel	Concrete tile		9 ABS	3					
	R PERFORAT	_			Gauzed wrap			8 Saw cut		11 Non	e (open h	nole)
	ntinuous slot	-	3 Mill slot		Wire wrapped			9 Drilled hole				
	uvered shutter		4 Key punched		Torch cut			10 Other (spe	ecify)			
SCREEN-P	PERFORATED	INTERVA		15 ft. to								
			From	ft. to			ft. F	rom	ft.	to		ft.
GR	AVEL PACK II	NTERVAL		14 ft. to						to		ft.
							_	rom	ft.	to		ft.
				2 Cement grout		3 Bentonit		4 Other				
Grout Interv	vals From	1	ft. to 14	ft. From		ft. to		ft. From		ft. to		ft.
			le contamination:			1	0 Livest	tock pens	14 A	bandoned	water we	ell .
						11 Fuel storage 15 Oil well/ 0					s well	
	wer lines		5 Cess pool		wage lagoon			zer storage	16 O	ther (spec	ify below)
	atertight sewer	lines	6 Seepage p	oit 9 Fee	edyard			ticide storage				
Direction fro		CODE	1171	010010100			w many			(A)TEDVA		
FROM 0	0.4	CODE	Concrete	OLOGIC LOG	- FR	ROM	то		LUGGING	INTERVA	_3	
0.4	0.8		Fill – Sand									
		1		vn to brown to bro	wn							
0.8	15.5	1 1	•	nd sandy, caliche z								
15.5	21		Sand, very fine	to coarse grained								
21	25		Clay, gray mot	tling, silty, some sa	and							
		-										
		 										
		-										
7 CONTR	ACTOR'S OR	LANDOW	NER'S CERTIFIC	ATION: This water we	ell was (1) co	nstructed	(2) reco	nstructed, or (3)	plugged un	der my iuri	sdiction a	nd was
	on (mo/day/yr)			17/08								
			·	531				rue to the best of ecore was comp				
ł .	ousiness name		Gentechi	nical Services I				was comp	neteu on (M	o/uay/yr)		J, VO
				correct answers. Send		o Kansas D	gnature) Departmer	of Health and E	nvironment	Bureau of V	Vater, 100	0 S W
lacker	on St. Ste. 420	Toneka Ka	neae 66612-1367	Telephone: 913-296-55	545 Send one	e to MATE	D WELL	WAVER and reta	in one for you	ir records		