

1 LOCATION OF WATER WELL: County: Harvey Fraction: NE 1/4 SE 1/4 NW 1/4 Section Number: 24 Township Number: 23 Range Number: 1 EW

Distance and direction from nearest town or city street address of well if located within city:

2 WATER WELL OWNER: Jack Sims
RR#, St. Address, Box #: Tract #3 Morlings East
City, State, ZIP Code: Newton, KS 67117
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 7-17-94
Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft.
WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 7-17-94
Pump test data: Well water was 10 ft. after 1/2 hours pumping 20 gpm
Est. Yield 10 gpm: Well water was 10 ft. after 1/2 hours pumping 20 gpm
Bore Hole Diameter 11 in. to 80 ft. and 80 in. to 80 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 5 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 5 in. to 33 ft. Dia. 2.60 in. to PS1 1160 ft. Dia. 2.60 in. to PS1 1160 ft. Dia.
Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. PS1 1160
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 33 ft. to 80 ft. From 33 ft. to 80 ft.
GRAVEL PACK INTERVALS: From 10 ft. to 80 ft. From 10 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 10 ft. From 10 ft. to 80 ft. From 10 ft. to 80 ft. From 10 ft. to 80 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? Northwest How many feet? 80

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-17-94 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/year) 7-29-98
under the business name of Weninger Drilling by (signature) Karina Morrissey

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.