

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		<u>NE 1/4 NE 1/4 SE 1/4</u>	<u>1</u>	<u>T 23 S</u>	<u>R 11 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>In Quivira Refugia</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Board of Agriculture, Division of Water Resources Application Number:			
<u>Quivira Refugia - Hornbaker</u> <u>RT 3, Box 48A</u> <u>Stafford, KS 67578</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>34</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>16</u> ft. below land surface measured on mo/day/yr <u>10-27-92</u> Pump test data: Well water was <u>19</u> ft. after <u>1</u> hours pumping <u>30</u> gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. <u>8</u> in. to <u>3.6</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering <u>(2) Other (Specify below)</u> 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>S.K.C.A.</u> Was a chemical/bacteriological sample submitted to Department? Yes. No. <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel 3 RMP (SR) <u>(2) PVC</u> 4 ABS		5 Wrought iron 8 Concrete tile Welded 6 Asbestos-Cement 9 Other (specify below) Threaded. 7 Fiberglass			
Blank casing diameter <u>5</u> in. to <u>24</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>24</u> in., weight <u>2.37</u> lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>(2) PVC</u> 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped <u>(8) Saw cut</u> 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>24</u> ft. to <u>34</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>18</u> ft. to <u>36</u> ft., From ft. to ft.					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
<u>0</u> <u>18</u> <u>Sandy Br Silt</u>					
<u>18</u> <u>27</u> <u>F-C Sand</u>					
<u>27</u> <u>36</u> <u>Sand & Sm Gravel</u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-27-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>12-5-92</u> under the business name of <u>Miller Drilling</u> by (signature) <u>[Signature]</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					