

FISCHER

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STAFFORD	SW 1/4 SW 1/4 SW 1/4	28	T 23 S	R 11 E

Distance and direction from nearest town or city street address of well if located within city?

STAFFORD 3/4 3E NE NORTHSIDE.

2 WATER WELL OWNER: DUKE DRILLING CO. INC.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: BOX 823	Application Number: T86-170
City, State, ZIP Code: GREAT BEND, KS 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 16 ft.
	Depth(s) Groundwater Encountered 1. 10 ft. 2. 16 ft. 3. 32.5-86 ft.
	WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 3-25-86
	Pump test data: Well water was 10 ft. after 16 hours pumping 32.5-86 gpm
	Est. Yield 77.8 gpm Well water was 40 ft. after 40 hours pumping 40 gpm
Bore Hole Diameter: 7.718 in. to 40 ft. and 40 in. to 40 ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued xy Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 20 ft. Dia 20 in. to 20 ft. Dia 20 in. to 20 ft.			11 Other (specify)
Casing height above land surface 12 in. weight 2.65 lbs./ft. Wall thickness or gauge No. 2.14			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE: 1/8	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft. From 20 ft. to 40 ft. From 20 ft. to 40 ft.			
GRAVEL PACK INTERVALS: From 10 ft. to 40 ft. From 10 ft. to 40 ft. From 10 ft. to 40 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 40 ft. From 40 ft. to 40 ft.				
What is the nearest source of possible contamination: NONE	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	TOP SOIL			
2	3	BROWN CLAY			
3	8	WHITE & TAN CLAY			
8	33	SAND & GRAVEL			
33	37	- W/CLAY MIX			
37	40	CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-25-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 4-6-86 under the business name of FEISER WATER WELL SERV. INC. by (signature) Budash
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.