

ISOC-1

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: Stafford; Fraction: 1/4 SW 1/4 SE 1/4 NW 1/4; Section Number: 1; Township No.: T 23 S; Range Number: R 12 []E [X]W; Street/Rural Address of Well Location; Global Positioning System (GPS) information: Latitude: 38.044492 N; Longitude: 98.365149 W; Elevation: ; Datum: [] WGS 84, [] NAD 83, [] NAD 27; Collection Method: [] GPS unit, [] Digital Map/Photo, [] Topographic Map, [] Land Survey; Est. Accuracy: [] <3 m, [] 3-5 m, [] 5-15 m, [] >15 m

3 LOCATE WELL WITH AN "X" IN SECTION BOX: N, W, E, S; 1 mile scale bar

4 DEPTH OF COMPLETED WELL: 18 ft.; Depth(s) Groundwater Encountered (1) 6.0 ft. (2) ft. (3) ft.; WELL'S STATIC WATER LEVEL: ft. below land surface; Pump test data: Well water was ft. after hours pumping gpm; EST. YIELD: gpm; Well water was ft. after hours pumping gpm; Bore Hole Diameter 8.25 in. to 18 ft. and in. to ft.; WELL WATER TO BE USED AS: [] Public water supply, [] Geothermal, [] Injection well, [] Domestic, [] Feedlot, [] Oil field water supply, [] Dewatering, [] Other; [] Irrigation, [] Industrial, [] Domestic-lawn & garden, [X] Monitoring well; Was a chemical/bacteriological sample submitted to Department? [] Yes [X] No; If yes, mo/day/yr sample was submitted; Water well disinfected? [] Yes [X] No

5 TYPE OF CASING USED: [] Steel [X] PVC [] Other; CASING JOINTS: [] Glued [] Clamped [] Welded [X] Threaded; Casing diameter 2 in. to 8 ft., Diameter in. to ft., Diameter in. to ft.; Casing height above land surface 36 in., Weight lbs./ft., Wall thickness or gauge No. sch 40; TYPE OF SCREEN OR PERFORATION MATERIAL: [] Steel, [] Stainless Steel, [X] PVC, [] Other; [] Brass, [] Galvanized Steel, [] None used; SCREEN OR PERFORATION OPENINGS ARE: [] Continuous slot, [X] Mill slot, [] Gauze wrapped, [] Torch cut, [] Drilled holes, [] None; [] Louvered shutter, [] Key punched, [] Wire wrapped, [] Saw cut, [] Other; SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft., From ft. to ft., From ft. to ft.; GRAVEL PACK INTERVALS: From 6 ft. to 18 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: [] Neat cement, [] Cement grout, [X] Bentonite, [] Other; Grout Intervals: From 0 ft. to 6 ft., From ft. to ft., From ft. to ft.; What is the nearest source of possible contamination: [] Septic tank, [] Lateral lines, [] Pit privy, [] Livestock pens, [] Insecticide storage, [] Other; [] Sewer lines, [] Cesspool, [] Sewage lagoon, [] Fuel storage, [] Abandoned water well; [] Watertight sewer lines, [] Seepage pit, [] Feedyard, [] Fertilizer storage, [] Oil well/gas well; Direction from well; Distance from well

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-1 silt, yellow brown, damp, sandy; 1-6 sand, brown to yellow brown, very fine, moist, silty; 6-15 sand, brown, very fine to medium, wet, petroleum odor; 15-18 clay, dark gray, firm, silty, moist petroleum odor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was [X] constructed, [] reconstructed, or [] plugged under my jurisdiction and was completed on (mo/day/year) 1/23/14 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 604. This Water Well Record was completed on (mo/day/year) 2/13/14 under the business name of Environmental Priority Service, Inc. by (signature) P. A. Wright

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html