•	WELL R			WWC-5		vision of Wate	I I			
Original Record Correction Chan								Well ID		
1 LOCATION OF WATER WELL:				Fraction		ction Numbe		1 -		
County: 5774ford										
Business' direction from powers tourner intersection). If at our more										
Address:										
Audress.				/2520	•		700,03	WESTOR		
			State: KS	ZIP: 67578		Shed				
3 LOCAT WITH "		4 DEPTH	OF COM	IPLETED WELL:		t. 5 Latitu	de:	(decimal degrees)		
i .	Depth(s) Groundwater Encountered: 1)							(decimal degrees)		
ì	N   2) ft. 3) ft., or 4) □						: □ WGS 84 □ NAD			
	X			TER LEVEL: Z.			for Latitude/Longitude:			
<b>'</b>	1	below land surface, measured on (mo-day-yabove land surface, measured on (mo-day-yabove land surface)			/-yr)	GI احر		)		
NW	NE	Pump test d	and surface, ata: Well w	ater was	fi		(WAAS enabled? ☐ ' and Survey ☐ Topograp	Yes ∐ No)		
w <del>                                   </del>	E			pumping						
'				vater was						
Sw	SE		after hours pumping			6 Flores	tion: A	□ C		
	S	Estimated Yield: 1.0.0gpm			01	6 Elevation:ft. ☐ Ground Level ☐ TOC Source: ☐ Land Survey ☐ GPS ☐ Topographic Map				
1	-	Bore Hole I	Bore Hole Diameter: 10.5%. in. to95			ft. Other				
1 mile  in. to ft.										
1. Domestic:							10.  Oil Field Water Supply: lease			
	☐ Household 6. ☐ Dewatering: how									
☐ Lawn &				echarge: well ID		☐ Ca	☐ Cased ☐ Uncased ☐ Geotechnical			
				g: well ID			12. Geothermal: how many bores?			
_ =				al Remediation: well I			Closed Loop    Horizontal    Vertical			
			] Air Sparge ] Recovery	•	Extraction		b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted:										
				C D Other	CASI	NG IOINTS	M Glued Clamped	□ Welded □ Threaded		
8 TYPE OF CASING USED: Steel PVC Other										
Casing height above land surface										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ Fiberglass     ☐ Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous Slot ☑ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From										
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other										
Grout Intervals: From										
Nearest source of possible contamination:										
Septic Tank							C			
	✓ Sewer Lines       Cess Pool       Sewage Lagoon       Fuel Storage       Abandoned Water Well         Watertight Sewer Lines       Seepage Pit       Feedyard       Fertilizer Storage       Oil Well/Gas Well									
Direction from well? Distance from well? 275										
10 FROM	TO		ITHOLO	GIC LOG	FROM	TO	LITHO. LOG (cont.) or I	PLUGGING INTERVALS		
0	18	SANO		0 Soll						
18	38	TAN	Clay							
38 65 90	65	FINE	_	Sand						
6.5	90	COAYS	e 500	nd						
70	94	LARGE	910	rife						
94	75	TAM	cisy		Notes:					
					- rotes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was A constructed. Treconstructed or I plugged										
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)										
Kansas Wa	ter Well Cor	tractor's Lic	ense No	6.7 This W	ater Well Re	cord was con	nnleted on moseay-yea	ar) 8 -14-15		
				water wel						
INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submit fee of \$400 for each constructed well along with one (white) copy to Kansas  Department of Health and Environment, Bureau of Water, Goology Section, 1000 SW Jackson St., Suite 420, Toneka, Kansas 66612-1367. Telephone (785) 296-3565.										

KSA 82a-1212

Revised 9/10/2012

Visit us at http://www.kdheks.gov/waterwell/index.html