

1) LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stafford	SE ¼ NW ¼ SW ¼	33	T 23 S	R 13 E/W

Distance and direction from nearest town or city street address of well if located within city?

Main and 6th Street, St. John, Kansas

2	WATER WELL OWNER:	Jim's Amoco	
	RR#, St. Address, Box #	113 West 4 th Street	
	City, State, ZIP Code	St. John, Kansas 67576	
			Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W

E

N

S

NW NE

SW SE

X

4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: 1904.53

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was NA ft. after hours pumping gpm

Est. Yield NA gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 50 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:		3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass		Threaded. ☒	
Blank casing diameter 2 in. to 40 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface -4.8 in. weight Sch 40 lbs./ft.		Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL		7 PVC		10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:		From 40 ft. to 50 ft.	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:		From 38 ft. to 50 ft.	From ft. to ft.	From ft. to ft.	
		From ft. to ft.	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft to 20 ft, From 20 ft to 33 ft, From ft to ft
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
..... Former UST Basin
Direction from well? Southwest How many feet? 1200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Clay, Dark Brown			
5	30	Sand, Red Brown			
30	50	Sand, Red Brown			
					MW20D , Tag # 00295648 , Flushmount
					Project Name: Greenfield - Jim's Amoco
					GeoCore # 830 , KDHE # U1 093 11433

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/28/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 1/19/00 under the business name of GeoCore Services, Inc. by (signature) [Signature]