


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County <u>Stafford</u>	<u>NE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	<u>33</u>	T <u>23</u> S	R <u>13</u> E <u>(W)</u>

Distance and direction from nearest town or city street address of well if located within city?
112 & 113 West 4th. St John, KS.

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Application Number:
City, State, ZIP Code	
<u>Jim's Amoco</u>	
<u>112 W. 4th</u>	
<u>St John, Ks.</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>29 1/2'</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 <u>20'</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>20.53</u> ft. below land surface measured on mo/day/yr <u>5-8-98</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm Well water was ft. after hours pumping gpm
	Bore Hole Diameter <u>8 1/2"</u> in. to <u>29 1/2'</u> ft. and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <u>No</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	Welded X
Blank casing diameter <u>2.375</u> in. to <u>9 1/2'</u> ft. Dia			Threaded <u>X</u>
Casing height above land surface <u>Flush Mt.</u> in. weight lbs./ft. Wall thickness or gauge No. <u>SDR 13</u>			<u>Sch 40</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>7 PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<u>3 Mill slot</u>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>29 1/2'</u> ft. to <u>9 1/2'</u> ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From <u>29 1/2'</u> ft. to <u>8'</u> ft.	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	<u>2</u> Cement grout	3 Bentonite	4 Other
Grout Intervals:	From <u>8'</u> ft. to <u>3 1/2'</u> ft.	From <u>3 1/2'</u> ft. to <u>0'</u> ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	<u>11</u> Fuel storage
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage
Direction from well <u>Southwest</u>				How many feet? <u>60'</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Grass-brn -blk silty sandy fill w/ brick, concrete rubble dry, no odor			
5	8	Gray-Lt gray clay to silty clay, firm to stiff, no odor moist			
8	18	Lt. brn silty sand grading in color to lt gray silty sand damp, slight odor, fine grained			
18	29.5	Dk gray fine-coarse sand, wet at 19.5' mod odor, well graded			

F.M. OK'd by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, <u>(2)</u> reconstructed, or <u>(3)</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>5-6-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>5-11-98</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>
