

1

LOCATION OF WATER WELL:
County: Stafford

Fraction
NE $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$

Section Number
33

Township Number
T 23 S

Range Number
R 13 EW

2


WATER WELL OWNER:
RR#, St. Address, Box #
City, State, ZIP Code

Jim's Amoco
112 W. 4th
St John, Ks.

Board of Agriculture, Division of Water Resources
Application Number:

3

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4

DEPTH OF COMPLETED WELL: 28' ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 18' ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 18.65 ft. below land surface measured on mo/day/yr 5-8-98
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm Well water was ft. after hours pumping gpm
Bore Hole Diameter 8 1/2" in. to 28' ft., and in. to ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5

TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)
Blank casing diameter 2.375 in. to 8' ft. Dia. in. to ft. Dia. in. to SDR 13 ft.
Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. Sch 40
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 28' ft. to 8' ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 28' ft. to 6' ft. From ft. to ft.
From ft. to ft. From ft. to ft.

6

GROUT MATERIAL:
1 Neat cement 3 Cement grout 5 Bentonite 4 Other
Grout Intervals: From 6' ft. to 3' ft. From 3' ft. to 0 ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? South How many feet? 10'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.5	Concrete			
.5	2.5	Brn sandy clay, moist, no odor			
		fine grained sand			
2.5	8	Gray-brn clay, stiff, slt odor			
		moist			
8	10.5	Dk gray-blk banded clayey sand			
		strong odor, damp, fine graded			
10.5	28	Gray to blk fine-coarse			
		grained sand strong odor,			
		well graded, dry			
		Wet at 18.5', strong odor			

F.M. OK'd by J. Taylor

7

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-8-98 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-11-98
under the business name of JB Environmental Drilling by (signature) James Becker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.