

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: Stafford Fraction 1/4 NW 1/4 NW 1/4 SW 1/4 Section Number 6 Township No. T 23 S Range Number R 13 [] E [X] W
Street/Rural Address of Well Location: 4 1/2 North, 2 West of St. John
Global Positioning System (GPS) information: Latitude: 38.079012 Longitude: 098.802580
2 WATER WELL OWNER: M & N Farm Ent RR#, Street Address, Box #: PO Box 307 City, State, ZIP Code: St. John, KS 67576
Datum: [] WGS 84, [X] NAD 83, [] NAD 27
Collection Method: [X] GPS unit, [] Digital Map/Photo, [] Topographic Map, [] Land Survey

3 LOCATE WELL WITH AN 'X' IN SECTION BOX: N W E S
4 DEPTH OF COMPLETED WELL 100 ft.
Depth(s) Groundwater Encountered (1) 41 ft. (2) ft. (3) ft.
WELL'S STATIC WATER LEVEL 41 ft. below land surface measured on mo/day/yr 11-16-15
Pump test data: Well water was... EST. YIELD N/A gpm. Bore Hole Diameter 10 in. to 100 ft.
WELL WATER TO BE USED AS: [] Public water supply, [] Geothermal, [] Injection well, [] Domestic, [] Feedlot, [] Oil field water supply, [] Dewatering, [X] Other (Specify below) Stock
Irrigation, [] Industrial, [] Domestic-lawn & garden, [] Monitoring well
Was a chemical/bacteriological sample submitted to Department? [] Yes [X] No
Water well disinfected? [X] Yes [] No

5 TYPE OF CASING USED: [] Steel [X] PVC [] Other
CASING JOINTS: [X] Glued [] Clamped [] Welded [] Threaded
Casing diameter 5 in. to 100 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface 18 in., Weight SDR 26 lbs./ft., Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL: [] Steel [] Stainless Steel [X] PVC [] Other (Specify)
[] Brass [] Galvanized Steel [] None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: [] Continuous slot [] Mill slot [] Gauze wrapped [] Torch cut [] Drilled holes [] None (open hole)
[] Louvered shutter [] Key punched [] Wire wrapped [X] Saw cut [] Other (specify)
SCREEN-PERFORATED INTERVALS: From 100 ft. to 80 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 100 ft. to 20 ft., From ft. to ft.

6 GROUT MATERIAL: [] Neat cement [] Cement grout [X] Bentonite [] Other
Grout Intervals: From ft. to ft., From 20 ft. to 0 ft., From ft. to ft.
What is the nearest source of possible contamination: [] Septic tank [] Lateral lines [] Pit privy [] Livestock pens [] Insecticide storage [X] Other (specify below)
[] Sewer lines [] Cesspool [] Sewage lagoon [] Fuel storage [] Abandoned water well
[] Watertight sewer lines [] Seepage pit [] Feedyard [] Fertilizer storage [] Oil well/gas well None
Direction from well Distance from well

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows include: 0-3 Sandy top soil, 3-11 Soft, sandy clay, 11-18 Hard, brown clay, 18-41 Brown clay, 41-56 Sandy clay- white & tan, 56-70 Sandy gravel- small & med, 70-100 Gravel- small, med, clean, coarse.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was [X] constructed, [] reconstructed, or [] plugged under my jurisdiction and was completed on (mo/day/year) 11-16-15 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 11-17-15 under the business name of Rosencrantz- Bemis Ent Inc by (signature) Tara Altep

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html