

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County STAFFORD	SW 1/4 SW 1/4 SW 1/4	33	T 23 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

315 N. PEARL

2 WATER WELL OWNER: TWILA DELP	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 315 N. PEARL	Application Number:
City, State, ZIP Code: ST. JOHN, KS 67576	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
--	---

	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 9 in. to ft. and in. to ft.
WELL WATER TO BE USED AS:	
☒ 1 Domestic ☐ 2 Irrigation ☐ 3 Feedlot ☐ 4 Industrial ☐ 5 Public water supply ☐ 6 Oil field water supply ☐ 7 Lawn and garden only ☐ 8 Air conditioning ☐ 9 Dewatering ☐ 10 Monitoring well ☐ 11 Injection well ☐ 12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes ☒ No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
☒ PVC	7 Fiberglass		Threaded

Blank casing diameter: 5 in. to 50 ft. Dia. in. to ft. Dia. in. to ft.
Casing height above land surface: 24 in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-cement
1 Steel	8 RMP (SR)	11 Other (specify)
2 Brass	9 ABS	12 None used (open hole)
3 Stainless steel		
4 Galvanized steel		
5 Fiberglass		
6 Concrete tile		

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			

SCREEN-PERFORATED INTERVALS:	From 50 ft. to 60 ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From 23 ft. to 60 ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ 3 Bentonite	4 Other
Grout intervals: From 3 ft. to 23 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well
1 Septic tank	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	13 Insecticide storage	NONE KNOWN
4 Lateral lines		
5 Cess pool		
6 Seepage pit		
7 Pit privy		
8 Sewage lagoon		
9 Feedyard		

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TOP SOIL			
3	22	CLAY			
22	38	GRAVEL			
38	42	CLAY			
42	60	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 7-29-94 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 462 This Water Well Record was completed on (mo/day/yr) 8-13-94
under the business name of SAM'S WATER WELL SERVICE by (signature) <i>Lore Rayburn</i>