

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 Section Number 33 Township Number T 23 S Range Number R 13 EW
 County: STAFFORD
 Distance and direction from nearest town or city street address of well if located within city?

111 W. 1st.

2 WATER WELL OWNER: JIM HICKS

RR# St. Address, Box # : 111 W. 1st.


Board of Agriculture, Division of Water Resources

City, State, ZIP Code : ST. JOHN, KS. 67576

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:



Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 24 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 9 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued X Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Weilded

XX PVC

4 ABS

7 Fiberglass

Threaded

Blank casing diameter: 5 in. to 50 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface: 24 in. weight lbs. ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

XX PVC

10 Asbestos-cement

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

11 Other (specify)

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

1 Continuous slot

XX Mill slot

6 Wire wrapped

9 Drilled holes

2 Louvered shutter

4 Key punched

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 23 ft. to 60 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

X3 Bentonite

4 Other

Grout intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination.

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

NONE KNOWN

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TOP SOIL			
3	21	CLAY			
21	36	GRAVEL			
36	41	clay			
41	60	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was XX constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-28-94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 462This Water Well Record was completed on (mo/day/yr) 8-13-94

Under the business name of

SAM'S WATER WELL SERVICE

by (signature)

Lora Rayburn