

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		<u>NE 1/4 NW 1/4 NE 1/4</u>	<u>3</u>	T <u>23</u> S	R <u>14</u> EW
Distance and direction from nearest town or city street address of well if located within city?					
<u>3 West 2N 3 West 4N 200yds W South side of Rd of St John</u>					
2 WATER WELL OWNER: <u>Ronie Duggert</u>					
RR#, St. Address, Box #: <u>R+1 Box 101</u>					
City, State, ZIP Code: <u>St John KS 67576</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>75</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1</u> <u>21</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>21</u> ft. below land surface measured on mo/day/yr <u>11-12-99</u>			
		Pump test data: Well water was <u>30</u> ft. after <u>1</u> hours pumping <u>50</u> gpm			
		Est. Yield <u>60</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10.75</u> in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Stock</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>0</u> PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded					
Blank casing diameter <u>5</u> in. to <u>55</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>2.4</u> in., weight <u>Sch 40</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>55</u> ft. to <u>75</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>75</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other					
Grout Intervals: From <u>5</u> ft. to <u>25</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Fine Sand			
5	16	Brown sticky clay			
16	32	Sandy clay			
32	49	Sand + Gravel + white clay			
49	65	Sand medium			
65	74	Sand + Gravel			
74	80	Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-12-99</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>473</u> This Water Well Record was completed on (mo/day/yr) <u>11-18-99</u>					
under the business name of <u>Tyler Water Well Inc</u> by (signature) <u>Dustin Lyle</u>					