			ATER WELL RE	CORD Form	WWC-5		a-1212 I		Alimaha :	T D	Mumbar	
LOCATION		TER WELL:	Fraction	እ ፕ ‹ፖ	CTAT		on Numb 10		Number		Number	
County:	Staffo				SW	74		T 23	<u> </u>	R 14	W E/W	
			town or city stre	et address of well	I if locate	a within city	Y					
		ohn, Ks.										
WATER	WELL OW	NER: Stan	Copeland									
RR#, St. Ac	ddress, Box	_{(# :} 1122	? Pinecroft	-					_	Division of V	Vater Resource	
City, State,	ZIP Code	: Suga	rland, TX	77478					on Number:			
LOCATE	WELL'S LC	CATION WITH	4 DEPTH OF	COMPLETED W	ELL	7.7	ft. ELE	VATION: UNKI	nown			
	N SECTION		Depth(s) Grou	indwater Encounte	ered 1.	. 5.0		ft. 2	ft. 3		ft.	
	<u> </u>		WELL'S STAT	IC WATER LEVEL	5.0) ft. belov	land surf	ace measured on	mo/day/yr	.04/02/0	3	
A	1 1	! !	Pu	ımp test data: Wo	ell water	was	f	t. after	hours	pumping	gpm	
	NW -	- NE	Est. Yield	.12gpm: We	ell water	was	f	t. after	hours	oumping	gpm	
	1	ī		meter 8								
₩ W	1	E		R TO BE USED A								
-		! ! .	1 Domesti			field water			12 (Other (Speci	fy below)	
X	CIA	- SE	1	4 Industrial				10 Monitoring we				
	300 -	- SE				•	-					
♦	i	i	Was a chemica	al/bacteriological sai			artment? Y	'es <u>. No</u>	; If yes, r	no/day/yrs s	ample was sub	
<u> </u>	S		mitted				Wa	ter Well Disinfect	ed? Yes		No	
TYPE O	F BLANK C	CASING USED		-				CASING				
1 Steel		3 RMP (S	•	6 Asbestos-Ce		•		•				
2 PVC		_4 ABS		7 Fiberglass								
Blank casi	ng diamete	r	in. to 5.	7 ft., Dia	<u>.</u>	in.	to	ft., Dia		in. to	<u></u>	
Casing he	ight above	land surface	12	. in., weight	2 . 8		lk	s./ft. Wall thickne	ss or gauge N	o Sch.	. 40	
						7.PVC			Asbestos-cen			
TYPE OF SCREEN OR PERFORATION MATERIAL 1 Steel 3 Stainless steel				5 Fiberglass	5 Fiberglass 8 RMP (SR)				11 Other (specify)			
	2 Brass 4 Galvanized steel				6 Concrete tile 9 ABS			12 1	None used (o			
SCREEN	OR PERF	DRATION OPE	ENINGS ARE:	į	5 Gauze	wrapped		8 Saw cut		11 None	(open hole)	
	inuous slot		/lill slot	(6 Wire w	rapped		9 Drilled hol	es		,	
2 Louv	ered shutte	er 4 K	Key punched	•	7 Torch	cut		10 Other (spe	ecify)		ft.	
SCREEN-	PERFORA	TED INTERVA	ALS: From	57 f	t. to	7.7	ft., Fr	om	ft. [.]	to	ft.	
			From	[.] f	t. to		ft., Fr	om	ft. '	to	<i>.</i> ft.	
(GRAVEL P	ACK INTERVA	LS: From	20 f	t. to	77	ft., Fr	om	ft	to	ft.	
				f								
6 GROUT		L: 1 Neat	cement	2 Cement grou	t	3 Bentoni	te	4 Other				
Grout Inte	rvals: Fro	m Q	ft. to20	🤾	n	ft.	to	ft., From		ft. to		
What is th	e nearest :	source of possi	ible contaminati	on:			10 Liv	estock pens	14 /	Nbandoned v	vater well	
	1 Septic tank 4 Lateral lines				7 Pit privy			el storage	15 (15 Oil well/Gas well		
2 Sewer lines 5 Cess pool				8 Sewage lagoon				•	16 (16 Other (specify below)		
3 Watertight sewer lines 6 Seepage p			=					ecticide storage				
Direction f	•	, iiiles 0 000)	page pit	0.1	oodyara			nany feet?		A-5-1 £1-1-1 1-		
		r	LITUOLOGIO I			EDOM .			PLUGGING I	NTEDVALC		
FROM	ТО		LITHOLOGIC	LUG		FROM	то		LUGGING I	VIERVALS		
0	7	top sand	1									
7	48	clay										
48	53	fine sar	nd									
53	77		gravel									
55	, ,	Don't dire	2 924702									
											*	
								1				
					+							
								<u> </u>				
								1				
				ATION: This water								
											d belief. Kansas	
Water Well	Contractor	's Licence No.	186	This Wa	ater Well	Record was	complete	ed on (mo/dav/vr)	04/06/	03		
	usiness na	_{me of} Kell	ly's Water	Well Servi	ce, I	nc.		(signature)			ad	
IIInger the h			_		-		- V	Commission of the				