594 13872 Stock WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction 1/4 SW 1/4 SW 1/4 SE 1/4	Section Number Township No. Range Number
County: Stafford Street/Rural Address of Well Location;	1	Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here		Latitude: 38.059349 (in decimal degrees)
Approximately 4 miles north and 5.5 r	Longitude: -98.866355 (in decimal degrees)  Elevation: Unknown	
2 WATER WELL OWNER: Robert Harris		Collection Method:
RR#, Street Address, Box #: 582 NW 60th Ave. City, State, ZIP Code : St. John, KS 67576		GPS unit (Make/Model: WAAS
	Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: < 3 m, 3-5 m, 5-15 m, >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 67 ft.		
SECTION BOX:  Depth(s) Groundwater Encountered (I)  WELL'S STATIC WATER LEVEL 19.21 ft. below land surface measured on mo/day/yr 05/06/16 ft.		
Pump test data: Well water was not checked ft. after hours pumping gpm		
W -NW EST. YIELD gpm. Well water was ft. after hours pumping gpm in. to 70 ft., and in. to ft.		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)  Irrigation Industrial Domestic-lawn & garden Monitoring well Stock		
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No		
S If yes, mo/day/yr sample was submitted Water well disinfected? X Yes No		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded Other (Specify)  Casing diameter 5 in. to 50 ft., Diameter 5 in. to 65 ft., Diameter in. to ft.  Casing height above land surface 24 in., Weight 2.36 lbs./ft., Wall thickness or gauge No. 214		
Casing diameter 5 in. to 11., Diameter in. Diameter		
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)		
Brass Galvanized Steel None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft., From ft. to ft.		
From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 20 ft. to 70 ft., From ft. to ft.		
GRAVEL PACK INTERVALS:		U ft., From ft. to ft. ft., From ft. to ft.
6 CROUT MATERIAL: Neat cement Cement grout Rentonite Other		
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:		
Septic tank Lateral lin		
☐ Watertight sewer lines ☐ Seepage p	oit 🔲 Feedyard 🔲 Fertilizer st	orage Oil well/gas well None Known
Direction from well FROM TO LITHOLOG	Distance IC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 5 Topsoil	TROM	ETHO. DOG (COIL.) OF TEOGRAPH INTERVALS
5 36 Brown, sandy, clay 36 61 Sand & gravel, mediu	m to fine	
61 70 Cement sand, hard w		
streaks		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 05/06/16 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 05/10/16		
under the business name of Clarke Well & Equipment, Inc. by (signature)  INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdheks.gov/waterwell/index.html.  KSA 82a-1212		