


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>	$\frac{1}{4}$ C $\frac{1}{4}$ SE $\frac{1}{4}$	<u>1</u>	T <u>23</u> S	R <u>14</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

5 north, 2 west of St. John

2 WATER WELL OWNER: <u>Merlin Grimes</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>2600 Canterbury</u>	Application Number: <u>39,093</u>
City, State, ZIP Code : <u>Great Bend, Ks. 67530</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>120</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>.34</u> ft. below land surface measured on mo/day/yr <u>2-21-89</u>
	Pump test data: Well water was <u>.77</u> ft. after <u>1 1/2</u> hours pumping <u>1200</u> gpm
	Est. Yield <u>1200</u> gpm: Well water was <u>.81</u> ft. after <u>1 1/2</u> hours pumping <u>1300</u> gpm
	Bore Hole Diameter <u>.30</u> in. to <u>120</u> ft., and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	<u>2 Irrigation</u> 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u>; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <u>HTH</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 <u>PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>.16</u> in. to <u>.80</u> ft., Dia			Threaded
Casing height above land surface <u>.12</u> in., weight <u>SDR 32.5</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 <u>PVC</u>	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 <u>Louvered shutter</u>	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>.80</u> ft. to <u>120</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>.20</u> ft. to <u>120</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	<u>NONE</u>
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Sandy top soil			
3	12	Fine sand			
12	24	Fine sand clay mixed			
24	42	Clay			
42	53	Sand and gravel			
53	56	Clay			
56	105	Sand and gravel			
105	107	Clay			
107	110	Fine sand			
110	120	Sand and gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-3-89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>6-20-89</u> under the business name of <u>Rosencrantz-Bemis</u> by (signature) <u>Fredia Radson</u>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.