


1 LOCATION OF WATER WELL: County: Stafford	Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 13	Township Number T 23 S	Range Number R 14 E/W
---	----------------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1 1/2 miles west and 3 miles north of St. John

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	James D. Soden Route 3 - Box 4 St. John, KS 67576	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 86 ft. ELEVATION: unknown Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 2-11-91 Pump test data: Well water was not ch'd. ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 5 in. to 8 1/4 in. to in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No
--	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued X Clamped Welded Threaded
Blank casing diameter 5 in. to 6 1/4 in. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 24 in. weight 2.36 lbs./ft. Wall thickness or gauge No. 214	TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched	5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 64 ft. to 84 ft. From ft. to ft. From ft. to ft. From ft. to ft.	GRAVEL PACK INTERVALS: From 28 ft. to 36 ft. From ft. to ft. From 42 ft. to 86 ft. From ft. to ft.	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug	
Grout Intervals: From ft. to ft. From 3 ft. to 28 ft. From 36 ft. to 42 ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	
Direction from well? northeast	How many feet? 190.5'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil, sandy			
2	12	Brown clay			
12	17	Clay, tan			
17	25	Sand and gravel, medium to coarse			
25	28	Clay, hard, brown			
28	37	Sand, medium to fine			
37	41	Clay, tan			
41	62	Sand, medium to fine			
62	65	Clay, brown to tan			
65	86	Sand, medium to coarse			
86		Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-11-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 2-26-91 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Charles W. Clarke</i>
--