


BEAVER A-1		WATER WELL RECORD		Form WWC-5	KSA 82a-1212	
1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	
County: STAFFORD		NE 1/4 SE 1/4 NW 1/4	16		T 23 S	
Distance and direction from nearest town or city street address of well if located within city?		Range Number R 14 EW				
2 WATER WELL OWNER:		WATER BEAVER, ST. JOHN, KS.				
RR#, St. Address, Box # : RT1 BOX 183B		Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : GREAT BEND, KS 67530		Application Number: T84-985				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 11-30-84				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm; Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 7 7/8 in. to 65 ft. and in. to ft.				
		WELL WATER TO BE USED AS:				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped				
1 Steel 3 RMP (SR)		Welded				
2 PVC 4 ABS		Threaded				
Blank casing diameter 5 in. to 45 ft. Dia		in. to ft. Dia in. to ft.				
Casing height above land surface 12 in., weight 2.05 lbs./ft. Wall thickness or gauge No. 2-14						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: 48		5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 45 ft. to 15 ft. From ft. to ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 35 ft. to 65 ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL:		4 Other				
1 Neat cement 2 Cement grout 3 Bentonite						
Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	5	TOP SOIL				
5	15	SANDY CLAY				
15	20	CLAY				
20	25	SANDY CLAY				
25	30	FINE SAND				
30	60	GRAVEL				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-30-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 789 This Water Well Record was completed on (mo/day/yr) 12-9-84 under the business name of REISER WATER WELL SERV. INC. by (signature) Rudolph J. Reiser						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						