

1

LOCATION OF WATER WELL:

County: Stafford

Distance and direction from nearest town or city street address of well if located within city?
Approx. 3 1/2 mi. west and 2 3/4 mi. north of St. John, KS

2

WATER WELL OWNER: Ward Beaver

RR#, St. Address, Box # : Route 1

City, State, ZIP Code : St. John, KS 67576

3

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

W

SW

SE

E

S

4

DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: unknown

Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft.

WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 7/8/85

Pump test data: Well water was not ck'd ft. after hours pumping gpm

Est. Yield 550 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 24 in. to 50 ft., and in. to ft.

WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5

TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR)
2 PVC 4 ABS

5 Wrought iron 8 Concrete tile
6 Asbestos-Cement 9 Other (specify below) Welded X
7 Fiberglass Threaded

Casing joints: Glued Clamped

Blank casing diameter 16 in. to 30 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 36.87 lbs./ft. Wall thickness or gauge No. 219

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify) Doerr Bridge Slot

SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 50 ft., From ft. to ft., From ft. to ft.

6

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage FIELD

Direction from well? ALL How many feet?

FROM

TO

LITHOLOGIC LOG

FROM

TO

LITHOLOGIC LOG

0

18

Fine sand topsoil & sandy clay

18

44

Sand & gravel, med. to fine to coarse, clean, loose

44

50

White & brown clay

7

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/8/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 7/23/85 under the business name of Clarke Well & Eq., Inc. by (signature) Clarke Well & Eq., Inc.

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4