

1 LOCATION OF WATER WELL: COUNTY: STAFFORD FRACTION: NW 1/4 NW 1/4 NE 1/4 SECTION NUMBER: 25 TOWNSHIP NUMBER: 23 S RANGE NUMBER: 14 E	
DISTANCE AND DIRECTION FROM NEAREST TOWN OR CITY STREET ADDRESS OF WELL IF LOCATED WITHIN CITY: ST JOHN IN 2 1/2 W SOUTHSIDE	
2 WATER WELL OWNER: HUSKY DRILLING CO INC. WILBUR L. RADKE, ST. JOHN KS	
RR#, ST. ADDRESS, BOX #: 555 NORTH WOODLAWN	
CITY, STATE, ZIP CODE: WICHITA, KS 67208	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	
4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: 45 ft.	
WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr: 9-14-82	
PUMP TEST DATA: WELL WATER WAS 2 ft. after 2 hours pumping	
EST. YIELD: gpm: WELL WATER WAS 2 ft. after 2 hours pumping	
BORE HOLE DIAMETER: 7 7/8 in. to 70 ft. and in. to	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
WAS A CHEMICAL/BACTERIOLOGICAL SAMPLE SUBMITTED TO DEPARTMENT? YES.....NO.....; IF YES, MO/DAY/YR SAMPLE WAS SUBMITTED	
WATER WELL DISINFECTED? YES.....NO.....	
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped	
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded	
7 Fiberglass Threaded	
Blank casing diameter: 5 in. to 50 ft. Dia. in. to ft. Dia. in. to ft.	
Casing height above land surface: 12 in. weight: 2.65 lbs./ft. Wall thickness or gauge No. 21.4	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement	
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)	
9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1/8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 40 ft. to 70 ft. From ft. to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.	
What is the nearest source of possible contamination: NONE 10 Livestock pens 14 Abandoned water well	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? How many feet?	
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG	
0 15 SANDY CLAY	
15 20 SAND	
20 45 SANDY CLAY	
45 70 GRAVEL	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-14-82 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 9-21-82	
under the business name of MEISER WATER WELL SERV. by (signature) Rudolph Meiser	
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.	