

1 LOCATION OF WATER WELL: County: STAFFORD		Fraction NW 1/4 NW 1/4 NE 1/4	Section Number 25	Township Number T 23 S	Range Number R 14 E
Distance and direction from nearest town or city street address of well if located within city? ST. JOHN 1N2 1/2 W SOUTHSIDE					
2 WATER WELL OWNER: HUSKY DRILLING CO INC. RR#, St. Address, Box #: 555 N. WOODLAWN STE 114 City, State, ZIP Code: WICHITA, KS 67208			Board of Agriculture, Division of Water Resources Application Number: [REDACTED]		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: 70 ft.			
		Depth(s) Groundwater Encountered 1. 40 ft. 2. 70 ft. 3. 9-13-82 ft.			
		WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr 9-13-82			
		Pump test data: Well water was 77/8 in. to 70 ft. after 7 hours pumping 7 gpm			
		Est. Yield 77/8 gpm; Well water was 70 ft. after 7 hours pumping 7 gpm			
Bore Hole Diameter 77/8 in. to 70 ft. and 70 in. to 70 ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted No					
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No			
1 Steel		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
2 PVC		6 Asbestos-Cement	9 Other (specify below)	Welded Threaded	
3 RMP (SR)		7 Fiberglass			
4 ABS					
Blank casing diameter 5 in. to 5 ft., Dia. 5 in. to 5 ft., Dia. 5 in. to 5 ft.		Casing height above land surface 5 in., weight 5 lbs./ft. Wall thickness or gauge No. 5			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut			
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	11 None (open hole)
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 70 ft. to 40 ft., From 40 ft. to 13 ft., From 13 ft. to 3 ft.			
GRAVEL PACK INTERVALS:		From 70 ft. to 40 ft., From 40 ft. to 13 ft., From 13 ft. to 3 ft.			
6 GROUT MATERIAL:		3 Bentonite			
1 Neat cement		4 Other			
Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 70 ft.		10 Livestock pens			
What is the nearest source of possible contamination: NONE		14 Abandoned water well			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
70	40	soil surface, sandy 4cuft.			
40	13	sandy soil 3.6cuft.			
13	3	cement neat 1.3cuft.			
by phone 3-11-83 DWB					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-1-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 3-3-83 under the business name of REISER WATER WELL SERV. INC. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E

SEC.

NW 1/4

NW 1/4

NW 1/4

NE 1/4

NE 1/4

MJP