	Mo	nitor	WATER	WELL RECORD	Form W	WC-5	KSA 82				
LOCATION OF WATER WELL:		Fraction				on Numbe			Range Number	Ì	
	County: PaunEE Distance and direction from nearest town of				NE 1/4	1 3	32	1 7 23	5 s	R 15W EA	<u> </u>
Distance a						city?					
		Miles Nor	thurst of	Macksvi	lle						
2 WATER	R WELL OW	NER: North	ern Natural	l Gas							
RR#, St. /	Address, Bo	x # : 12 Na	tional Bank	, blog	TV -10	~				Division of Water Resou	
City, State	, ZIP Code	: 100 7	. Fillmore,	Amavillo.	17 23	1101		Applicat	ion Number:		
J LOCATI	E WELL'S L IN SECTIO	OCATION WITH A	DEPTH OF CO	MPLETED WELL		77	. ft. ELEV	'ATION:			
AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1											1
WELL'S STATIC WATER LEVEL ft. below land surface measured on m											
Pump test data: Well water was ft. after hours pumpin											
Est. Yield gpm: Well water was ft. after hours pu									· =		
Bore Hole Diameterin. toft., andin. to									. to	ft.	
₹							Injection well	\frac{7}{4}			
ī L	_ sw	5	1 Domestic					_	ewatering 12 Other (Specify below)		
	1	;	2 Irrigation	-			_	only to Monitoring well			
1 L	Was a chemical/bacteriological sample submitted to Department? YesNo; If yes, mo/da							, mo/day/yr sample was	sub∤ 🖁		
<u> </u>		S	mitted				W	ater Well Disinfe	cted? Yes	No	9
5 TYPE (OF BLANK (CASING USED:		5 Wrought iron	8 0	Concrete	e tile	CASING .	JOINTS: Glue	d Clamped	··· 🗖
1 Ste		3 RMP (SR	()	6 Asbestos-Ceme	ent 9 (Other (s	specify belo	ow)	Weld	led	
2 PV		4 ABS	^~	7 Fiberglass					Thre	aded	
Blank casi	ng diameter	·	in. to	ft., Dia		in. to .		ft., Dia		in. to	. ft.
Casing he	ight above la	and surface	ir	n., weight		<u></u>	lbs	s./ft. Wall thicknes	ss or gauge N	lo	
TYPE OF	SCREEN O	R PERFORATION	I MATERIAL:			7 PVC		10 A	Asbestos-ceme	ent	
1 Ste	eel	3 Stainless	steel	5 Fiberglass		8 RMP	(SR)	11 (Other (specify)		→
2 Br	ass	4 Galvanize	ed steel	6 Concrete tile		9 ABS		12 1	None used (op	en hole)	
SCREEN	OR PERFO	RATION OPENING	SS ARE:	5 G	auzed wrapp	ped		8 Saw cut		11 None (open hole)	
1 Co	ontinuous sk	3 Mil	l slot	6 W	ire wrapped			9 Drilled hole	es		1
2 Lo	uvered shut	ter 4 Ke	y punched	7 To	orch cut	~ -		10 Other (spe	cify)		
SCREEN-	PERFORAT	ED INTERVALS:	From	. 23 ft. t	o	ゴ ヺ゛	ft., Fr	om	ft. 1	to	ft.
			From	<u></u> ft. t	ر	<u> </u>	ft., Fr	om	ft. 1	to to	ft. 📗
(GRAVEL PA	CK INTERVALS:	From	. .20 ft. t	o	33	ft., Fr	om	ft. 1	to	ft. ~
			From	ft. t	0		ft., Fr	om	ft. 1	to	ft.
	T MATERIAL			Cement grout		Bentoni					
Grout Inte	rvals: Fro	m	ft. to N. V	ft., From	8	. ft. to	5 2	. ft., From		ft. to	ft.
What is th	e nearest so	ource of possible of	contamination:				10 Live	estock pens	14 A	bandoned water well	
1 Se	eptic tank	4 Latera	ıl lines	nes 7 Pit privy			11 Fuel s		storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess poor			pool	of 8 Sewage lagoo		n 12 Fer		tilizer storage	16 C	Other (specify below)	F 8
3 W	atertight sew	ver lines 6 Seepa	ige pit	9 Feedyar	d		13 Inse	ecticide storage			>
Direction f	from well?						How m	any feet?			
FROM	то		LITHOLOGIC LO	og	FRO	ОМ	TO		PLUGGING I	NTERVALS	<u>v</u>
		MW	1 # 2								
O	33	Moist B	rown San	d, clay							
27	33	Wet, fir	re to Medi	ium San	d						
		•									
				.,,_,							
											-
			, , , , , , , , , , , , , , , , , , , ,								~ ~ ~
7 001-	DACTOR'S		'S CERTIFICATIO	N: This water		onetro ch	ed (2) ===	constructed or 15	a) plugged ::-	der my juriediation and	was
CONTI	HAUTUR'S	or Landowner √year)	S CEMILLICATIO							der my jurisdiction and	
			551					d on (mo/day/y/		lowledge and belief. Kai	
		's License No					by (sign			-J	··· ¾
			ted Envir								
INSTRU of Heal	ICTIONS: Use ty th and Environn	ypewriter or ball point p nent, Bureau of Water,	en. <u>PLEASE PRESS FIR.</u> Topeka, Kansas 66620-0	MLY and <u>PRINT</u> clearly 0001. Telephone: 913-2	y. Please fill in b 296-5545. Send	one to W	ATER WELL	OWNER and reven on	send top three te for your record	copies to Kansas Department s.	