

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Pawnee	Fraction $\frac{1}{4}$ 1/4CSW $\frac{1}{4}$	Section number 3	Township number T 23 S R	Range number 15 EW																														
2. Distance and direction from nearest town or city: 14 miles Southeast of Larned, KS Street address of well location if in city:			3. Owner of well: R.R. or street: City, state, zip code: Kansas Investment Properties c/o Kenneth Maechtlen Box 2281 Wichita, KS 67201																																
4. Locate with "X" in section below: N W E S 1 Mile Sketch map:			6. Bore hole dia. 24 in. Completion date 8-23-76 Well depth 80 ft.																																
5. Type and color of material <table border="1"><thead><tr><th></th><th>From</th><th>To</th></tr></thead><tbody><tr><td>top soil & sand</td><td>05</td><td>10</td></tr><tr><td>sandy clay</td><td>10</td><td>16</td></tr><tr><td>sand</td><td>16</td><td>27</td></tr><tr><td>brown clay & limestone</td><td>27</td><td>38</td></tr><tr><td>sand & gravel & thin clay streaks at 41, 48, & 67</td><td>38</td><td>75</td></tr><tr><td>brown clay</td><td>75</td><td>80</td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr></tbody></table>				From	To	top soil & sand	05	10	sandy clay	10	16	sand	16	27	brown clay & limestone	27	38	sand & gravel & thin clay streaks at 41, 48, & 67	38	75	brown clay	75	80										7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				From	To																														
			top soil & sand	05	10																														
			sandy clay	10	16																														
			sand	16	27																														
			brown clay & limestone	27	38																														
			sand & gravel & thin clay streaks at 41, 48, & 67	38	75																														
			brown clay	75	80																														
8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																			
9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 30.3 lbs./ft. Dia. 16 in. to 40 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth Gauge No. 7 ga.																																			
10. Screen: Manufacturer's name Doerr Type Double-slot Dia. 16" Slot gauge 1/8" Length 40' Set between 40 ft. and 80 ft. ft. and <input type="checkbox"/> ft. Gravel pack? yes Size range of material 3/8-200																																			
11. Static water level: <input type="checkbox"/> ft. below land surface Date 7-29-76 mo./day/yr. 20' 6"																																			
12. Pumping level below land surfaces: N/C ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield <input type="checkbox"/> g.p.m.																																			
13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/> mo./day/yr.																																			
14. Well head completion: Pitless adapter 12 inches above grade																																			
15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																																			
16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																			
17. Pump: Manufacturer's name FMC Corp/ Peerless Not installed Model number 12LS-4 HP 60 Volts 460 Length of drop pipe 70 ft. capacity 900 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																			
18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks: (Use a second sheet if needed)		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Clarke Well & Equ. Inc. 185 Business name License No. Address Great Bend, KS 67530 Signed D.W. Clarke Date <input type="checkbox"/> Authorized representative																																

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5