


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County PAWNEE Reno	Fraction CENTER SE 1/4 1/4 1/4 1/4	Section number 4	Township number 23 T S R	Range number 5 35 W E/W
2. Distance and direction from nearest town or city: Street address of well location if in city: 8 1/4 N. N. Macchard			3. Owner of well: Frankk Blodgett R.R. or street: City, state, zip code: Arlington, Kansas 67514			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 28 in. Completion date 5-19-77 Well depth 74 ft.		
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Sandy soil		0	2	9. Casing: Material Transi Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 30 lbs./ft. Dia. 16 in. to 48 ft. depth Wall Thickness: inches or Dia. 16 in. to 48 ft. depth gage No. 3/16 1/8		
Fine sand		2	5	10. Screen: Manufacturer's name Johnson Type sawed Dia. 16 Slot/gauze 3/16 Length 26 Set between 48 ft. and 74 ft. ft. and ft. Gravel pack? yes Size range of material 1/8-1/4		
Clay		5	10	11. Static water level: mo./day/yr. 17 ft. below land surface Date 10-7-76		
Fine sand		10	20	12. Pumping level below land surfaces: 37 ft. after 12 hrs. pumping 800 g.p.m. 41 ft. after 1 hrs. pumping 1000 g.p.m. Estimated maximum yield 1400 g.p.m.		
Fine sand and clay		20	30	13. Water sample submitted: mo./day/yr. <input type="checkbox"/> Yes <input type="checkbox"/> No Date		
Med. sand and clay		30	35	14. Well head completion: <input type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade		
Med. sand		35	50	15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
Med. to coarse sand		50	60	16. Nearest source of possible contamination: ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Med sand		60	70	17. Pump: Not installed Manufacturer's name Western Land Roller Model number 55-12 CM HP 60 Volts 440 Length of drop pipe 50 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
Coarse sand		70	72	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Darling Drilling Co. 189 Business name License No. Address 1211 W. 4th, Hutchinson, Ks. Signed Donald J. Darling Date 5-19-77 Authorized representative		
Clay		72	72 1/2			
SODIUM CHLORIDE. 55.0 PPM						
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5