

CAMPBELL #1


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: PAWNEE	C 1/4 SE 1/4 SW 1/4	7	T 23 S	R 15 E

Distance and direction from nearest town or city street address of well if located within city?

200K 3 1/4 E NORTHSIDE.

2 WATER WELL OWNER: D. R. LAUCK OIL CO. INC.	CAMPBELL, LARNED, KS.
RR#, St. Address, Box #: 221 S. BROADWAY SUITE 400	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: WICHITA KS 67202	Application Number: T84-177

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 35 ft.
	Depth(s) Groundwater Encountered 1. 27 ft. below land surface measured on mo/day/yr 3-21-84
	WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 3-21-84
	Pump test data: Well water was 77/8 in. to 60 ft. after 60 hours pumping 3-21-84 gpm
	Est. Yield 77/8 gpm: Well water was 60 ft. after 60 hours pumping 3-21-84 gpm
	Bore Hole Diameter 77/8 in. to 60 ft. and 60 in. to 60 ft.
	WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes 3-21-84 No 3-21-84 ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes 3-21-84 No 3-21-84

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued 3-21-84 Clamped 3-21-84
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 40 ft., Dia 40 in. to 40 ft.			
Casing height above land surface 12 in., weight 2-65 lbs./ft. Wall thickness or gauge No. 214			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE: 48	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft.			
GRAVEL PACK INTERVALS: From 27 ft. to 60 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft.				
What is the nearest source of possible contamination: NONE				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	6	SANDY EARTH			
6	15	SANDY CLAY			
15	25	GRAVEL			
25	35	CLAY			
35	60	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-21-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 3-28-84 under the business name of REISER WATER WELL SERV. INC. by (signature) Rudolph Reiser
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.