

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Pawnee		NE 1/4 SE 1/4 SW 1/4		30		T 23 S		R 15 E/W	
Distance and direction from nearest town or city street address of well if located within city? 3 3/4 East & 2 3/4 South of Zook KS Approximately									
2 WATER WELL OWNER: Kansas Corporation Commission									
RR#, St. Address, Box # : 302 W. McArtor Road					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Dodge City, KS 67801					Application Number: N/A				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 86 ft. ELEVATION: unknown							
		Depth(s) Groundwater Encountered 1. N/C ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL N/C ft. below land surface measured on mo/day/yr Pump test data: Well water was not ch'd ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .6 in. to 86 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X...; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
		5 TYPE OF BLANK CASING USED:							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued.....Clamped..... 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded..... 7 Fiberglass Threaded..... Blank casing diameter 2 in. to 83 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 24 in., weight 427 lbs./ft. Wall thickness or gauge No. 091							
		TYPE OF SCREEN OR PERFORATION MATERIAL:							
		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)..... 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify).....							
SCREEN-PERFORATED INTERVALS: From 73 ft. to 83 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 69 ft. to 86 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite "Holeplug"									
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 69 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) sinkhole 13 Insecticide storage									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	26	Topsoil, Fine Sand							
26	37	Clay soft, Sandy							
37	39	Sand							
39	46	Clay-white & Sandy Brown							
46	78	Sand & Gravel Fine to med w/ thin clay streaks							
78	83	Sand & Gravel fine -coarse w/ streak cemented sand @ 83'							
83	86	Clay Brown & Tan							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 12/27/88 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>David W. Clarke</i>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T 23

R 15

E/W

SEC 36

1/4

1/4

1/4