

WUWM #1 WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Pawnee Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 32 Township Number T 23 S Range Number R 16W E/W

Distance and direction from nearest town or city street address of well if located within city? 3 S of Zook, Kansas

2 WATER WELL OWNER: Walter Martin, Jr. Sterling Drilling Co. Well #1 RR#, St. Address, Box #: Route 2 Box 1006 Board of Agriculture, Division of Water Resources City, State, ZIP Code: Larned, KS 67550 Pratt, KS 67124 Application Number: 940464

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the bottom-left section]

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Unknown

Depth(s) Groundwater Encountered: 1. 38 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 38 ft. below land surface measured on mo/day/yr 11/25/94

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 60 gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter: 7 7/8 in. to 80 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply X 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC X 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

7 Fiberglass Threaded

Blank casing diameter: 5 in. to 60 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC X 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 5 Gauzed wrapped 8 Saw cut X 11 None (open hole)

2 Louvered shutter 3 Mill slot 6 Wire wrapped 9 Drilled holes

4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 80 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite X 4 Other

Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well X

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? South How many feet? 60

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

80 20 Sand and Gravel

20 3 Bentonite

3 0 Top Soil

Casing cut off 3' below ground level and removed.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 19, 1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 151 This Water Well Record was completed on (mo/day/yr) 12/20/95 under the business name of Sterling Drilling Company by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.