

1 LOCATION OF WELL:		Fraction	Form: WWS-0		Section Number	Township Number	Range Number
County: Pawnee	NE 1/4 SE 1/4 SE 1/4	2	T 23	S	R 16W	E/W	
Distance and direction from nearest town or city street address of well if located within city? 1 3/4E, 1N of Zook, Ks.							
2 WATER WELL OWNER: Herb Bowman							
RR#, St. Address, Box # : RR 2 Box 72				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Larned, KS 67550				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 76 ft. ELEVATION: unknown					
		Depth(s) Groundwater Encountered 1 55 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 55 ft. below land surface measured on mo/day/yr 04/22/04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 5 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 56 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 56 ft. to 76 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 23 ft. to 35 ft. From 40 ft. to 76 ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 23 ft. From 35 ft. to 40 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? Northwest How many feet? 15 13 Insecticide storage barn							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0	3	top soil					
3	22	clay					
22	32	sand and gravel					
32	56	clay					
56	76	clay with sand and gravel streaks					
		sand rock bottom					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/22/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 186 This Water Well Record was completed on (mo/day/yr) 04/23/04 under the business name of Kelly's Water Well Service, Inc. by (signature) Kelly's Water Well Service, Inc.							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							