KOLAR Document ID: 1583746

	WELL R			WWC-5 ge in Well Use			vision of Wat			 Well ID		
				Fraction			sources App. lection Numb		Township Numb		inge Number	
1 LOCATION OF WATER WELL: County:					1/4 1/4 1/4			1			∏E □W	
					/4	· ·	Street or Rural Address where well is located (if unknown, distance					
							irection from nearest town or intersection): If at owner's address, check here:					
Address:	and the state of t							n mie	isection). If at Owner	. s audiess,	, check here.	
Address:												
City:			State:	ZIP:								
	3 LOCATE WELL 4 DEPTH OF COMPLET						t 5 Tatit	ndo.			(4:1 4)	
	WITH "A" IN Donth (a) Crown devictor I				Encountered: 1) ft.			5 Latitude:				
	CHON BOX: ft 2)				ft., or 4) Dry Well			Datum: WGS 84 NAD 83 NAD 27				
Г					ΓER LEVEL: ft.			Source for Latitude/Longitude:				
			below land surface, measured on (mo-day-yr						unit make/model:)	
NW	NE	above la	☐ above land surface, measured on (mo-day-yr					(WAAS enabled? ☐ Yes ☐ No)			,	
	Pump test da	Pump test data: Well water was ft.				□ I	☐ Land Survey ☐ Topographic Map					
w	XE	after	after hours pumpinggpm					Online Mapper:				
sw	SE	Well water was ft.										
5,,,	I I	after hours pumping gpm					6 Eleve	6 Elevation:ft. ☐ Ground Level ☐ TOC				
		Estimated Yield:gpm Bore Hole Diameter:in. toft				£1		Source: Land Survey GPS Topographic Map				
							Other					
1 mmc												
7 WELL WATER TO BE USED AS: 1. Domestic: 5. □ Public Water Supply: well ID												
☐ Household Supply: Well ID												
			echarge: well ID				☐ Cased ☐ Uncased ☐ Geotechnical					
				g: well ID								
	2. ☐ Irrigation 2. ☐ Irrigation 3. ☐ Mointoinig. weil iD 9. Environmental Remediation:							thermal: how many bores? Closed Loop				
3. ☐ Feedlo								b) Open Loop Surface Discharge Inj. of Water				
4. Industr	Injection				13. Other (specify):							
4. Industrial Recovery Injection 13. Other (specify):												
Water well disinfected? \square Yes \square No												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to												
Casing height above land surface in. Weight												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)												
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)												
☐ Louve	red Shutter	☐ Key Punch	ned 🔲 W	ire Wrapped	☐ Sa	ıw Cut	None (Open I	Hole)				
SCREEN-F	PERFORATE	ED INTERVA	ALS: Fron	n ft. to .		ft., From	ft. t	о	ft., From	ft. t	o ft.	
G:	RAVEL PAC	CK INTERVA	ALS: Fron	n ft. to .		ft., From	ft. t	о	ft., From	ft. t	o ft.	
									ft. to	ft.		
	rce of possible			potential source								
☐ Septic			Lateral Line			_	Livestock P			cide Storag		
Sewer			Cess Pool				Fuel Storage		Abando			
☐ Waterti	ight Sewer Lin		Seepage Pit		yard		Fertilizer St	orage	e □ Oil We	II/Gas Wel	1	
☐ Other (Specify)												
10 FROM	TO		ITHOLOG		OIII W	FROM	ТО				NG INTEDVALS	
TO LINOIM	10	<u>L</u>	ATTIOLOG	JIC LOU		TROM	10	LII	110. LOG (cont.) 01	LUUUII	10 II TEK VALO	
	+											
	+											
	+											
	+											
	+					Notes:	1					
						110163.						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was _ constructed, _ reconstructed, or _ plugged												
under my jurisdiction and was completed on (mo-day-year)												
Kansas Wa	ter Well Con	tractor's Lice	ense No	Th	is Wa	ater Well Re	cord was co	mple	eted on (mo-day-ye	ear)		
	under the business name of											
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.												
_				Vater, Geology Sect	10n, 10	JUU SW Jackso	n St., Suite 420	, Тор	eka, Kansas 66612-136			
Visit us at <u>h</u>	ttp://www.kdhe	<u>ks.gov/waterwel</u>	<u>I/1ndex.html</u>							K	SA 82a-1212	