


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pawnee		NE 1/4 N 1/4 SE 1/4	12	T 23 S	R 17 EAW
Distance and direction from nearest town or city street address of well if located within city? 2 1/2 west, 1/2 north of Zook, Ks.					
2 WATER WELL OWNER:		Raymond Frick			
RR#, St. Address, Box #:		Rt. 2- Box 31			
City, State, ZIP Code:		Larned, Ks. 67550			
		Board of Agriculture, Division of Water Resources Application Number: 25647			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 62 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 52 ft. 2. 30 ft. 3. 6-23-95 ft. WELL'S STATIC WATER LEVEL 52 30 ft. below land surface measured on mo/day/yr 6-23-95 Pump test data: Well water was 52 ft. after 1 1/2 hours pumping 500 gpm Est. Yield 500 gpm: Well water was 52 ft. after 1 1/2 hours pumping 500 gpm Bore Hole Diameter 28 in. to 62 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 16 in. to 42 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 12 in., weight SDR 32.5 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 42 ft. to 62 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 62 ft. to 20 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 20 ft. to 4 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage none					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	10	Brown clay			
10	22	Fine sand w/ some streaks of clay			
22	26	Sand and gravel			
26	28	Sand rock			
28	30	Brown clay w/ sand rock mixed			
30	40	Sand rock			
40	42	White clay			
42	62	Sand and gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-5-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 7-11-95 under the business name of Rosencrantz-Bemis by (signature) Fredia Rodson					