## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:  Pawaee 1/4 1/45 W/4 30 1 23 5 R /7  2. Distance and direction from nearest town or city: #5  Street address of well location if in city: #5  4. Locate with "X" in section below:  Sketch map:  Township number 1 Township	se rotary ustry ck
Street address of well location if in city:  4. Locate with "X" in section below:  Sketch map:  Sketch map:  6. Bore hale dia. 30 in. Completion date	se rotary ustry ck
Street address of well location if in city:  4. Locote with "X" in section below:  Sketch mop:  6. Bore hole dia. 30 in. Completion dote — Well depth 25 ft. 5 - 27-  7. Cable tool _ Rotary _ Driven _ Dug	se rotary ustry ck
4. Locote with "X" in section below:  Sketch mop:  6. Bore hole dia	se rotary ustry ck
7Cable toolRotaryDrivenDugHollow rodJettedBoredKever.  8. Use:DomesticPublic supplyIndeK_IrrigationAir conditioningStorLawnOil field waterOth 9. Casing: MoterialSYAHeight: Above onThreadedWeldedXSurface/Surface	se rotary ustry ck
Hollow rodJettedBored _Kever.  8. Use:DomesticPublic supplyInd.    LawnOil field waterOthers.   Sw X SE   ThreadedWelded _XSurface/	ustry ck
Irrigation Air conditioning Store   Lawn Oil field water Other   Store Lawn Oil field water Other Other   Store Lawn Oil field water Other Other Other Other Other Other Other Other Ot	ck
Lawn _Oil field water _Oth  9. Casing: Material SY A Height: Above or	
Threaded Welded Surface	
1	_lbs./ft.
5. Type and color of material  Dio. 16 in. to 45ft. depth Wall Thickness: inc  Dio. 16 in. to 45ft. depth Wall Thickness: inc  Dio. 16 in. to 45ft. depth gage No. 3/1	
10. Screen: Manufacturer's name	
Top Soil-Clay 0 30 Type STEE! Dia. 16"	
5d Nd - Gravel 30 75 Slot/gauze 18" Length 30 75 Set between 45 ft. and 25	
ft. and	3 42
	/day/yr.
	7-77
12. Pumping level below land surfaces: ft. after hrs. pumping	g.p.m.
ft. after 4 hrs. pumping 800	g.p.m.
	-g.p.m. /day/yr.
Yes X No Date	
14. Well head completion: Pitless adapter	rade
15. Well grouted? Bentonite C	
Depth: From ft.	Sinciele 1
16. Nearest source of possible cantamination: Ma	one "
Well disinfected upon completion? Yes	No
17. Pump:  Manufacturer's name Goulds	~
Model number 3-/23 HP 60 Volt	
Туре:	g.p.m. 3
Submersible	cating to
(Use a second sheet if needed) Centrifugal Other	- S
18. Elevation: 19. Remarks: 20. Water well contractor's certification: This well was drilled under my jurisdiction and this re	report C
is true to the best of my knowledge and belief.	786
Topography:  Hill  Business night + 2 1 5 Lice	156 Bor 1 x
Slope Address X BYEST BEALG	代企
Valley Signed Authorized representative Date/	