

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		SW 1/4 SW 1/4 SE 1/4	8	T 23 S	R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 3 1/2 MILES N. of Holstead					
2 WATER WELL OWNER: Clinton Holdeman			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: RR #2 Burrton, KS 67020			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: ft.		
			Depth(s) Groundwater Encountered 1. 29 ft. 2. ft. 3. ft.		
			WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 1-18-88		
			Pump test data: Well water was 31 ft. after 1 1/2 hours pumping 30 gpm		
			Est. Yield 30 gpm: Well water was ft. after hours pumping gpm		
Bore Hole Diameter 11 in. to 48 ft. and in. to ft.			WELL WATER TO BE USED AS:		
			5 Public water supply 8 Air conditioning 11 Injection well		
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 13 Stock		
Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted			Water Well Disinfected? Yes No		
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 5 in. to 38 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 18 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped factory 8 Saw cut .032 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
3 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 38 ft. to 48 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 15 ft. to 48 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 15 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? West How many feet? 120'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Loam to fine sand			
5	9	dune sand			
9	15	red brown clay			
15	21	sand & brown clay - layered			
21	25	sandy clay			
25	29	grey clay			
29	44	sand - med to coarse			
44	48	sandy brown clay to dark grey			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-18-88 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 457 This Water Well Record was completed on (mo/day/yr) 2-3-88					
under the business name of United Water Well & Pump by (signature) Raul Bouchard					