


1 LOCATION OF WATER WELL: County: HARVEY Fraction: NE 1/4 SE 1/4 SE 1/4 Section Number: 10 Township Number: T 23 S Range Number: R 2 W E/W

Distance and direction from nearest town or city street address of well if located within city? 3 mile NORTH HALSTEAD KS

2 WATER WELL OWNER: EMERY YOST Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: R#1 Application Number:
City, State, ZIP Code: HALSTEAD KS 67056

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 54 ft. ELEVATION: 417/84 ft.
Depth(s) Groundwater Encountered: 1 ft. 20 ft. 23 ft. 2 ft. 20 ft.
WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 4/17/84
Pump test data: Well water was 23 ft. after 2 hours pumping 20 gpm
Est. Yield 30 gpm: Well water was 23 ft. after 2 hours pumping 20 gpm
Bore Hole Diameter: 10 in. to 54 ft. and 54 in. to 54 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
Blank casing diameter: 5 in. to 44 ft. Dia. 160 in. to 160 ft. Dia. 160 in. to 160 ft. Dia. 160 in. to 160 ft. Dia.
Casing height above land surface: 2 in., weight 160 lbs./ft. Wall thickness or gauge No. 160
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 12 None used (open hole)
SCREEN-PERFORATED INTERVALS: From 44 ft. to 54 ft. From 44 ft. to 54 ft. From 44 ft. to 54 ft. From 44 ft. to 54 ft.
GRAVEL PACK INTERVALS: From 10 ft. to 54 ft. From 10 ft. to 54 ft. From 10 ft. to 54 ft. From 10 ft. to 54 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? NORTH How many feet? 45

LITHOLOGIC LOG

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	LOAM - RED BROWN CLAY			
15	35	RED BROWN CLAY			
35	40	LIGHT BROWN CLAY			
40	45	FINE SAND			
45	50	MED SAND			
50	54	COARSE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/17/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 175 This Water Well Record was completed on (mo/day/yr) 6/30/84 under the business name of Paul's Inc by (signature) Paul Buntline

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

BWM

SEC.

10

11

12

13

14

15

16