


1 LOCATION OF WATER WELL: County: HARVEY <b>079</b>	Fraction NE 1/4 SE 1/4 NE 1/4	Section Number 12	Township Number T 23 S	Range Number R 2 W <b>EW</b>
--	----------------------------------	----------------------	---------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3 West, 2 1/2 N. of Twin Bridges

Halstead, Kansas

2 WATER WELL OWNER: Betty Graham	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Box 18578	Application Number: /
City, State, ZIP Code: Wichita, Kansas	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 14 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 7-27-84 ✓
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 30 in. to 60 ft. and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glueg Jammed X
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 16 in. to 21 ft. Dia			11 Other (specify)
Casing height above land surface 12 in., weight 37 lbs./ft. Wall thickness or gauge No. 3/4"			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify)
1 Steel	3 Stainless steel	9 ABS	12 None used (open hole)
2 Brass	4 Galvanized steel		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 21 ft. to 60 ft.			
GRAVEL PACK INTERVALS: From 14 ft. to 60 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 14 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines	5 Cess pool	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	13 Insecticide storage	None Apparent	
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	20 01	Clay			
20	38 17	Medium to Coarse Sand and Gravel			
38	54 01	Blue Clay			
54	56 07	Fine Sand			
56	58 03	Medium Sand			
58	60 19	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-27-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11-15-84 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Cernold
---

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.