

1 LOCATION OF WATER WELL: County: Harvey		Fraction SE $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$		Section Number 14	Township Number T 23 S	Range Number R 2W E/W
Distance and direction from nearest town or city street address of well if located within city? 2 mi. N of Hwy 50 & Farmers Corner, $\frac{1}{2}$ E, $\frac{1}{4}$ S. Halstead, Kansas						
2 WATER WELL OWNER: Withroder, Roger		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box # : R#1 Box 27B		Application Number:				
City, State, ZIP Code : Halstead, Kansas 67056						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 9-30-91				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 11 in. to 85 ft., and in. to ft.				
		WELL WATER TO BE USED AS:				
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ; If yes, mo/day/yr sample was submitted				
5 TYPE OF BLANK CASING USED:		Casing Joints: Glued X Clamped				
1 Steel 3 RMP (SR)		Welded				
2 PVC 4 ABS		Threaded				
Blank casing diameter 5 in. to 65 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass		8 RMP (SR) 11 Other (specify)				
2 Brass 4 Galvanized steel 6 Concrete tile		9 ABS 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot		6 Wire wrapped 9 Drilled holes				
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 65 ft. to 85 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 24 ft. to 85 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy		11 Fuel storage 15 Oil well/Gas well				
2 Sewer lines 5 Cess pool 8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage None Apparent				
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	3	topsoil				
3	68	grey clay				
68	71	fine sand				
71	85	grey clay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 12-31-91 under the business name of Harp Well and Pump Service, Inc. by (signature) <i>Mary Arnold</i>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						