

1 LOCATION OF WATER WELL: County: HARVEY		Fraction N 1/4 NW 1/4 SE 1/4	Section Number 35	Township Number T 23 S	Range Number R 2 E (W)
Distance and direction from nearest town or city street address of well if located within city? 100 MAIN, HALSTEAD, KS mw-4					
2 WATER WELL OWNER: WILDA MOFFATT			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box # : 100 MAIN			Application Number:		
City, State, ZIP Code : HALSTEAD, KS 66056					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.9 ft. ELEVATION: 1393.19			
		Depth(s) Groundwater Encountered 1. 20.0 ft. 2. - ft. 3. - ft.			
		WELL'S STATIC WATER LEVEL 20.01 ft. below land surface measured on mo/day/yr 4-25-93			
		Pump test data: Well water was - ft. after - hours pumping - gpm			
		Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm			
		Bore Hole Diameter 8 in. to 25.5 ft. and - in. to - ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes - No X		If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes - No X					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 2 in. to 14.9 ft. Dia - in. to - ft. Dia - in. to - ft.		Casing height above land surface 33.5 in., weight - lbs./ft. Wall thickness or gauge No. 40		CASING JOINTS: Glued - Clamped -	
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement		Welded -	
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		3 Mill slot		9 Drilled holes	
2 Louvered shutter		4 Key punched		10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 24.9 ft. to 14.9 ft.		From - ft. to - ft.	
GRAVEL PACK INTERVALS:		From 25.5 ft. to 12.9 ft.		From - ft. to - ft.	
6 GROUT MATERIAL: 0 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 12.9 ft. to 0 ft. From - ft. to - ft. From - ft. to - ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
Direction from well? SE		How many feet? 250			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.0	TOPSOIL			
1.0	6.5	DARK BROWN SILTY CLAY			
6.5	8.5	BROWN SILTY CLAY (MOTTLED)			
8.5	22.0	Grey Brown Silty Clay			
22.0	24.0	Grey Lt. Brown SANDY SILTY CLAY			
24.0	25.5	Grey FINE GRAM SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 7/23/93 under the business name of Terracon Consultants Inc by (signature) <i>Richard D. M...</i>					