

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Harvey		SE 1/4 SE 1/4 SW 1/4		29		T 23 S		R 2 E/W	
Distance and direction from nearest town or city street address of well if located within city? Approximately 1 mile north and 3 miles west of Halstead									
2 WATER WELL OWNER:		City of Wichita							
RR#, St. Address, Box # :		455 N. Main				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Wichita, KS 67202				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 204 ft. ELEVATION: unknown							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL not ch'd. ft. below land surface measured on mo/day/yr Pump test data: Well water was not ch'd. ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 215 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering Basin 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recharge Well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
		5 TYPE OF BLANK CASING USED:							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . X . Clamped . 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . 7 Fiberglass Threaded. Blank casing diameter 2 in. to 55 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 24 in., weight .96 lbs./ft. Wall thickness or gauge No. .218							
		TYPE OF SCREEN OR PERFORATION MATERIAL:							
		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 55 ft. to 202 ft., From ft. to ft. From ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 54 ft. to 215 ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL:		1 Sand & Gravel 2 Cement grout 3 Bentonite 4 Other .. Bentonite Holeplug							
Grout Intervals: From 4 ft. to 4 ft., From ft. to ft., From 4 ft. to 54 ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None known How many feet?							
Direction from well?									
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	9	Sand, medium, fine, very fine		126	154	Sand and gravel, medium, fine, very fine			
9	14	Sand and gravel, medium, fine, very fine		154	164	Clay, tan			
14	39	Clay, gray, green		164	206	Sand and gravel, medium, fine, very fine			
39	45	Sand, medium, fine, very fine							
45	69	Clay, brown, sand streaks		206	209	Clay, dark green			
69	83	Sand and gravel, medium, fine, very fine		209	215	Shale, black			
83	104	Clay, green							
104	114	Sand and gravel, medium, fine, very fine							
114	118	Clay, green							
118	122	Sand and gravel, medium, fine, very fine							
122	126	Clay, green							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-19-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 10-27-99 under the business name of Clarke Well & Equipment, Inc. by (signature) <i>Clarke Well & Equipment, Inc.</i>									