

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	<u>SE 1/4 SE 1/4 SW 1/4</u>	<u>30</u>	T <u>23</u> S	R <u>2</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

1/2 Mi N, 3 1/2 W of Halstead - 16214 SW 24th

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	Application Number:
City, State, ZIP Code:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>115</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>3.1</u> ft. below land surface measured on mo/day/yr <u>11-29-00</u>
	Pump test data: Well water was <u>41</u> ft. after <u>1</u> hours pumping <u>25</u> gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter. <u>8</u> in. to <u>11.7</u> ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes. No. <u>X</u> ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. <u>X</u> Clamped.
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
☒ PVC	4 ABS	7 Fiberglass	Welded.
Blank casing diameter <u>5</u> in. to <u>9.5</u> ft., Dia. in. to ft., Dia. in. to ft.			Threaded.
Casing height above land surface. <u>12</u> in., weight <u>2.29</u> lbs./ft. Wall thickness or gauge No. <u>16.0</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	☒ Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS: From. <u>9.5</u> ft. to <u>115</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From. <u>23</u> ft. to <u>46</u> ft., From ft. to ft.			
	From. <u>51</u> ft. to <u>117</u> ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ Bentonite	4 Other
Grout Intervals: From. <u>3</u> ft. to <u>23</u> ft., From <u>46</u> ft. to <u>51</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	☒ Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>NW</u>			How many feet? <u>150</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	17	Gr Clay			
17	21	M Sand			
21	24	Br Clay			
24	37	Gr Clay			
37	46	F-M Sand			
46	51	Gr Clay			
51	91	F-M Sand			
91	115	M Sand			
115	117	Br Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-29-00</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>12-7-00</u> under the business name of <u>Miller Drilling</u> by (signature) <u>E. Miller</u>
--