71	572	24 wa	TER WELL RI	ECORD	Form \	WWC-5	KSA	82a-1212	ID No.	IW-3A	١					
LOCATI	ON OF WA	TER WELL:	Fraction					ction Numl		Town	ship Nu	mber	R	ange Nu		
County: F	larvey		NW	1/4 NV	V 1/4	NW	1/4	17		Т	23	s	R	2	E (W)	
Distance a	nd direction	ı from nearest t	own or city stre	eet addre	ss of well	if located	within o	ity?								
		es north and 3 n		alstead												
2 WATER	WELL OW	NER: City of W	/ichita													
RR#, St. A	ddress, Box	<#: 455 N. M	l ain								-		ivision	of Wate	r Resources	
City, State,		. Wichita,									cation No	umber:				
	NELL'S LO	DCATION WITH					_ 36	ft. ELE	EVATIO	N: unk	nown					
_ AN A I	N SECTION	N BOX.	Depth(s) Gro						ft. 2		on mold					
A X			WELL'S STAT	IC WATE	deter Wel	not checke	ed π. be	low land sui checked	ft offer	easured	on more	houre r			gpm	
	_ NW -	NE	Est. Yield _ U													
	!	1	Bore Hole Dia													
₩ W		E	WELL WATE				blic water			Air condi				ction well		
	i	i	1 Domesti		eedlot		field water		9	Dewateri	ina	1	2 Othe	er (specify	/ below)	
	- SW	SE	2 Irrigation	_	Industrial			wn & garden			-			ndex We		
♦		1	Was a chemica								,	If ves m				
<u> </u>	5		mitted	al/Dacterio	nogical sali	iipie subiii	itted to E				rfected?		io, aay, j		No ✓	
5 TYPE O	F BLANK C	ASING USED:		5 Wro	ught iron		8 Concr					NTS: Glue	ed 🗸	Clamp	oed	
1 Steel		3 RMP (SR)		6 Asb	estos-Ceme	ent	9 Other	(specify belo	w)							
②PVC		4 ABS		7 Fibe	-	_						Thre	aded			
Blank cas	ing diamete	r 2	in. to	24	ft., Dia			in. to		ft.,	Dia		in. t		ft	
Casing he	ight above	land surface	24	in., weig	ght 		.70		lbs./ft. \	Wall thic	kness o	r gauge N	lo 	.154	4	
TYPE OF	SCREEN	OR PERFORA	TION MATERI	AL:		(7) PVC				10 Asbe	stos-cemei	nt			
1 Stee	1	3 Stainless	steel	5 Fib	erglass		8 RMP	(SR)				(specify)				
	2 Brass 4 Galvanized steel 6 Concrete to							9 ABS			12 None used (open hole)					
		ORATION OPE				zed wrappe	∌d			Saw o		11	None (pen hole)	
	tinuous slot	_	Mill slot			wrapped				9 Drilled					ft.	
	vered shutter	4 ATED INTERVALS:	Key punched From	24	7 Torc	h cut . to	34	ft F	rom			ft. t	_			
301	EEN-FERFOR	ATED INTERVALS.	From			. to	27					ft t			£+	
	GRAVEL	PACK INTERVAL		19		. to	36					ft t	_		f+	
			From		ft	. to		ft., F	rom			ft. t	o		ft.	
6 GRO	UT MATER	IAL: 1 Neat	cement 2 Ce	ement grou	ıt 3 E	Bentonite			4 Othe	er Ber	ntonite Ho	leplug				
Crout Int	omialai Ero	•			ft., From			ft to		ft F	rom	8	ft. to	1	9 ft.	
	ervals: Fro ne nearest :		ft. to	8 	it., Pioni			t. to 10 Livestoo		-				d water w		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,										Oil well/Gas well						
2 Sewer lines 5 Cess pool						8 Sewage lagoon 12 Fertiliz				•				Other (specify below)		
	ertight sewer		Seepage pit		9 Fee			13 Insectici	-			None k		•	•	
	•		, .			•		How n	nany fe	et?						
Direction f FROM	TO	I	LITHOLOGIC	LOG			FROM	ТО	T		PLUC	GING IN	ITERV/	ALS		
0	4	Topsoil	21111020010					+				**				
4	19	Clay, gray, sa	andv. hard													
19	24	Clay, black, h			****											
24	36	Sand, mediur	n, fine, very fin	е												
								<u> </u>								
									+							
								 		· · · · · · · · · · · · · · · · · · ·						
-			*:					+					-			
								 	-	***						
		-						 	+							
								1	+					-		
7		L									(0) ::1			2-0-0		
		LANDOWNER'S	CERTIFICATION			(1) cons	tructed				(3) plugge				n and was elief. Kansas	
	on (mo/day	/year) 's License No	195	6-26-0		ater Well I	Record v	and this r vas comple				O THY KII		e and be	or. Nariodo	
under the b	ousiness na	me of Clarke V	Vell & Fauinme	nt Inc					by (sign		KL	110	(1)		<i>y</i>	
		writer or hell point po			DDINT closely	Diogeo fill in	hlanke un	derline or circle	the correc	t anewore	Send ton th	ree conies to	Kansas F	enartment	of Health and	