127	572	4 wa	TER WELL RE	CORD	Form WV	VC-5	KSA 8	2a-1212 ID N	· —	-7A			
LOCATION	ON OF WAT	TER WELL:	Fraction				Sec	tion Number	To	wnship Num	ber	Range Number	
County: H			SE 1/	011		SW 1/4		28	T	23	s	R 2 E	W
Distance ar	nd direction	from nearest to	own or city stree	et addres	s of well if I	located w	ithin ci	y?					
Approxim	ately 1 mile	north and 1 3/4	4 miles west of h	Haistead									
2 WATER	WELL OW	NER: City of W	/iohito										
ــــ RR#. St. Ad	dress. Box	# : 455 N. W	ncina Iain						Во	ard of Agricu	Iture, D	ivision of Water Res	sources
		. Wichita,								plication Nun			
		CATION WITH		COMPLI	ETED WEL	L 8	30	ft. ELEVAT	TION: L	ınknown			
	N SECTION		Depth(s) Grou					EL C		7.7.7.7.7.7.	ft. 3		 . ft.
- -	N						ft. beld			red on mo/day	//vr		
†	1		Pu	mn test o	tata: Well v	vater was	not	checked ft af	ter		hours p	umping	apm
	- NW _	- NE										umping	
1	1	!	Para Hala Diag	· &	3pm. wen v 6 :	valei was	8) # a	nd		nours p	in. to	- gp
M ₹		E								nditioning		Injection well	11.
7			WELL WATER			5 Public				-		•	.
	- swl -	- se	1 Domestic	3 F	eedlot	6 Oil fiel	d water	supply 9	9 Dewa	tering	12	2 Other (specify below	w)
	i l	1	2 Irrigation	4 Ir	ndustrial	7 Dome	stic (lav	n & garden) 1	0 Monit	oring well		Index Well	
<u> </u>	x l		Was a chemical	/bacteriol	ogical sampl	le submitte	d to De	partment? Yes_		No	yes, m	o/day/yrs sample w	as sub-
	S		mitted					Water		isinfected? Y			
5 TYPE O	F BLANK C	ASING USED:		5 Wrou	ight iron	8	Concre	te tile	C/	ASING JOINT	S: Glue	d 🗸 Clamped	
1 Steel		3 RMP (SR)		6 Asbe	stos-Cement	9	Other (specify below)			Weld	ed	
2)PVC		4 ABS		7 Fibe	rglass			 .			Threa	aded	
_	ing diameter	. 2	in. to	58	ft., Dia		ir	n. to	f	t., Dia		in. to	ft
	-	and surface	24		iht	.70				thickness or g			
_	_						PVC			10 Asbesto	-		
			TION MATERIA			_	RMP (2D)					
1 Steel		3 Stainless			erglass		ABS	5K)					
2 Brass		4 Galvanize		6 Cor	ncrete tile		ADS		9 0-	12 None u		•	
		RATION OPE			5 Gauzeo				8 Sa			None (open hole)	
	tinuous slot	_	Mill slot		6 Wire w					illed holes			ft.
	vered shutter		Key punched		7 Torch o				10 Ot	her (specify)			
SCR	EEN-PERFORA	ATED INTERVALS:	From	58	ft, to		78	ft., From			-		
			From	,	ft. t			ft., From			ft. to		ft.
	GRAVEL	PACK INTERVAL		41	ft. t		78	ft., From ft., From			ft. to		ft. ft.
			From			<u> </u>		11., FIOIII			- 11. 10	<u> </u>	
6 GRO	JT MATERI	AL: 1 Neat	cement 2 Ce	ment grout	t 3 Be	ntonite		4 0	Other	Bentonite Hole	olug		
Grout Int	ervals: Fro	m	ft. to		ft., From		ff	. to	ft	From	Λ	ft. to 41	ft.
			ble contamination		-			10 Livestock per			14 Ah	andoned water well	· '''
		•	Lateral lines		7 Pit priv	.n.	11 Fuel storage 15 Oil well/Gas well						
1 Sept				•	_								
2 Sew						ge lagoon						her (specify below)	
3 Wate	ertight sewer l	ines 6	Seepage pit		9 Feedy	ard		13 Insecticide sto	orage	-	None k	nown	
Direction f	rom well?							How many	feet?				
FROM	TO		LITHOLOGIC L	.OG		FI	ROM	то		PLUG	SING IN	ITERVALS	
0	4	Topsoil											
4	9	Clay, gray											
9	14	Clay, brown,	sandv										
14	17	Gravel and c		·									
17	27		avel, medium, fir	ne				 					
27	31	Clay, gray, da											
31	56	Clay, gray, di				<u> </u>							
56	79		evel, medium, fir	ne						-			
79	80						,						
19	00	Clay, gray, g	10011					 					
				 		 		 					
	<u> </u>							 -				<u>,,</u>	
	ļ							 					
<u> </u>	<u> </u>												
7 CONTRA	ACTOR'S OR	LANDOWNER'S	CERTIFICATION	This water	er well was	(1) constru	cted	(2) reconstruc	cted, or	(3) plugged	un	der my jurisdiction and	was
	on (mo/day			10-3-0		·						owledge and belief.	
			185			er Well Re	cord w	as completed o				1039/01/	
under the t	business na	me of Clarke V	Vell & Equipmer	nt, Inc.					signature	/ -/	Ph	Clark	
					PRINT clearly P	lease fill in hi	anke und	erline or circle the co	rrect answ			Kansas Department of Hea	alth and