7/3		75 W	ATER WELL RE	CORD	Form WV	NC-5		82a-1212 II		DW-03-0B-0				
LOCATI	ION OF WA	TER WELL:	Fraction				Se	ection Numb	er	Township N	lumber	Rai	nge Numb	$\overline{}$
County: 1			NE 1/			SW	1/4	8		T 23	S	R	2	E (W)
			town or city stree			located	within c	ity?						
			d 4 1/4 miles north	h of Hals	stead									
2 WATER	WELL OW	NER: City of W	/ichita											
RR#, St. A	ddress, Box	# :455 N. M	lain							Board of Ag	· ·	ivision o	of Water F	Resources
	, ZIP Code	Wichita, I			····					Application				
3 LOCATE	WELL'S LO	CATION WITH	4 DEPTH OF	COMPL	ETED WEL	L	41	ft. ELE	VATION	unknown				
AN "X"	IN SECTION	A BOX:	Depth(s) Grou						ft. 2		ft. 3			. ft.
WELL'S STATIC WATER LEVEL 22.22 ft. below land surface measured on mo/day/ Pump test data: Well water was not checked ft. after												· • • • • • • • • • • • • • • • • • • •		
	_ NW	I NE												
	1		Est. Yield un											
₽ W	1	E	Bore Hole Dian	neter	i	n. to	·	! f						ft.
- "	1	! -	WELL WATER	TO BE US	ED AS:	5 Pub	lic water	supply	8 Air	conditioning	1	1 Inject	ion well	
_	- sw -	SE	1 Domestic	3 F	eedlot	6 Oil f	ield wate	r supply	9 De	watering				
1 1	i x	ī	2 Irrigation	4 i	ndustrial	7 Don	nestic (la	wn & garden)	10 Mc	onitoring well		Obse	rvation W	ell
<u>Y</u>	1	1	Was a chemical	/bacterio	logical sampl	le submit	tted to D	epartment? Y	Yes	No √				
			mitted							Disinfected				
_	F BLANK C	ASING USED:	:	5 Wro	ught iron		3 Concr			CASING JO				
1 Steel		3 RMP (SR))	6 Asbe	estos-Cement	ę	9 Other	(specify below	v)					
②PVC		4 ABS		7 Fibe	-						Threa			
	sing diamete		in. to	19	ft., Dia			in. to		ft., Dia		in. to	454	f
Casing he	eight above	land surface	24	in., weig	ght		70	!	bs./ft. Wa	all thickness	or gauge N	0	.154	
TYPE O	F SCREEN	OR PERFORA	ATION MATERIA	L:		\overline{C}	PVC			10 Asb	estos-cemer	nt		
1 Stee	el	3 Stainless	s steel	5 Fib	erglass	8	3 RMP	(SR)		11 Oth	er (specify)			
2 Bras	S	4 Galvaniz	ed steel	6 Co	ncrete tile	٤	ABS			12 Nor	ne used (ope	n hole)		
SCREEN	OR PERF	PRATION OPE			5 Gauzeo	d wrappe	d		8	Saw cut	11	None (or	en hole)	
1 Cor	ntinuous slot	3) Mill slot		6 Wire wr	rapped				Drilled holes				<u></u>
2 Lou	vered shutter	4	Key punched		7 Torch o				10	Other (specify	/)			ft.
SCF	REEN-PERFOR	ATED INTERVALS:		19	ft. to		39	ft., Fr			ft. to	o 		ft.
	CDAVEL	DACK INTERVAL	From		ft. to			ft., Fr			ft. to			££
	GRAVEL	PACK INTERVA		10	ft. to		40	ft., Fr						
61			From					ft., Fr						
GRO	UT MATER	IAL: 1 Neat	t cement 2 Cen	nent grou	t 3 Ber	ntonite		•	4 Other	Bentonite H	loleplug			
Grout Int	ervals: Fro	m	ft. to		ft., From		1	t. to		ft., From	0	ft. to	10	ft.
What is the	he nearest :	source of possi	ible contaminatio	n:				10 Livestock				andoned	water well	
1 Sept	tic tank	4	4 Lateral lines		7 Pit priv	⁄y		11 Fuel stora	age		15 Oil	well/Gas	well	
2 Sew	er lines	5	5 Cess pool		8 Sewag	je lagoon	ı	12 Fertilizer	storage		16 Ot	her (spec	ify below)	
3 Wate	ertight sewer	ines 6	Seepage pit		9 Feedya	ard		13 Insecticid	le storage	None	known			
Direction t	from well?							How ma	any feet?	?				
FROM	ТО		LITHOLOGIC LO	og.			FROM	ТО	T		JGGING IN	ITERVA	LS	
0	5	Topsoil						+						
5	7	Clay, dark br	own hard		······································			<u> </u>						
7	16	Clay, light bro									<u> </u>			
16	25	Clay, dark gr							<u> </u>					
25	39	<u> </u>	e to fine with grav	el fine a	and clay stre	aks.								
		loose, gray	9.41	<u> </u>		<u></u>								
39	40	Clay, blue-gr	een, hard											
									1					
			W.V.											
														<u> </u>
7 CONTR	ACTORIC CO	LANDOMATERIA	CERTIFICATION	TL:		(1) 00000	ruoted	(2) rances	etrueted	Of (2) alves	and ···	dor en di	riadiation -	nd was
1	on (mo/day		CERTIFICATION:	3-15-0	_	(1) const	ructed			or (3) plugg			risdiction ar and belie	
		's License No	185	J- 1J-U		r Well R	Record w	and this re- vas complete					-05/2	
			Nell & Equipment	t Inc	-			•	by (signati	/	110 h	7/1	7/	 -
			en. <u>PLEASE PRESS FIF</u>		PRINT clearly. Pla	ease fill in	blanks. und			-		Kansas De	partment of F	lealth and
			66620-0001. Telephone											