

1 LOCATION OF WATER WELL: County: <u>Harvey</u>	Fraction: <u>S 1/4 SW 1/4 NE 1/4</u>	Section Number: <u>35</u>	Township Number: <u>T 23 S</u>	Range Number: <u>R 2 E W</u>	
Distance and direction from nearest town or city street address of well, if located within city? <u>1206 Red Bud Halstead, KS</u>					
2 WATER WELL OWNER: <u>Chris Beenal</u>					
RR#, St. Address, Box # City, State, ZIP Code: <u>1206 Red Bud Halstead, KS</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>110</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>45</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? <u>Yes</u> No			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5 1/2</u> in. to <u>90</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>12</u> in., weight <u>24</u> lbs./ft. Wall thickness or gauge No. <u>160 PSI</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-Cement			
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR)		11 Other (Specify)			
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify) ft.			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS:		From <u>90</u> ft. to <u>110</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>45</u> ft. to <u>110</u> ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From <u>3</u> ft. to <u>15</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? <u>12</u>			
Direction from well? <u>EAST</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	topsoil			
1	18	clay			
18	45	fine sand			
45	48	clay			
48	80	fine sand			
80	85	clay			
85	110	fine sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10/21/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>#746</u> This Water Well Record was completed on (mo/day/yr) <u>7/11/05</u> under the business name of <u>Wenger Drilling Inc.</u> by (signature) <u>a. wenger</u>					