

1 LOCATION OF WATER WELL: County: Harvey	Fraction SE 1/4 SE 1/4 NW 1/4	Section Number 34	Township Number T 23 S	Range Number R 2 EW	
Distance and direction from nearest town or city street address of well if located within city? From Halstead KS: 1 mile West					
2 WATER WELL OWNER: Weber Farms					
RR#, St. Address, Box # : 247 main st. City, State, ZIP Code : Halstead KS 67056			Board of Agriculture, Division of Water Resources Application Number: 37225		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 148 ft. ELEVATION: 14 ft.			
		Depth(s) Groundwater Encountered 1 ft. 14 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 3-30-06 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 800 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Dewatering 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel 2 PVC		3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)			
CASING JOINTS: Glued X Clamped Welded Threaded					
Blank casing diameter 16 in. to 88 ft., Dia 16 in. to ft., Dia in. to ft.					
Casing height above land surface 36 in., weight 16 lbs./ft. Wall thickness or gauge No. 1/2"					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass		3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From 88 ft. to 148 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 148 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout		3 Bentonite 4 Other			
Grout Intervals: From 3 ft. to 28 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) None Direction from well? Open Field How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	18	Clay			
20	25	Fine Sand			
25	50	Medium Sand			
50	60	Tan Clay			
60	90	Dark Clay			
90	95	Tan Clay			
95	107	Very Fine Sand			
107	125	Medium Sand			
125	132	Tan Clay			
132	135	Sand			
135	140	Tan Clay			
140	147	Medium Sand			
147	148	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-30-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 338 This Water Well Record was completed on (mo/day/yr) 3-31-06 under the business name of Premier Pump & Well Service Inc. by (signature) W. Weber					