47 WATER	8144 WELL	DW1-OB3 Shallow RECORD Form WWC-5 Division of Water Resources; App. No.	\neg	
		WATER WELL: Fraction Section Number Township Number Range Number		
	ty: Harve	y NW 1/4 SW 1/4 NW 1/4 8 T 23 S R 2 E (tion from nearest town or city street address of well if located Global Positioning Systems (decimal degrees, min. of 4 digital degrees)	\sim	
within	city? App	roximately 5 miles east and 2 3/4 miles north of Latitude: unknown	(3)	
Burrt		Longitude: unknown	_	
2 WATI	E R WELI St. Addre	L OWNER: City of Wichita Elevation: unknown Datum: N/A	_	
		SS, Box # : 455 N. Main Code : Wichita, KS 67202 Datum: N/A Data Collection Method: N/A	-	
3 LOCA				
1	ATION			
1	I AN ''X''	-1 TYPE THE COLUMN TO THE POPULATION 18.44 18.44 18.44 18.44		
SECTION BOX: N WELL'S STATIC WATER LEVEL 10.44 ft. below land surface measured on mo/day/yr. 324-00. Pump test data: Well water was not checked ft. after hours pumping from the pumping for the pumping from t				
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm	1	
xNW	/NE		ĺ	
w		E 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below		
sw		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Observation Well	~~	
		Was a chemical/bacteriological sample submitted to Department? Yes No V If yes, mo/day/y	rs	
	S	Sample was submitted Water well disinfected? Yes No		
5 TYP	E OF CAS	SING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued 🗸 Clamped		
_		RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded		
2 PVC 4 ABS 7 Fiberglass Threaded Rlank casing diameter 2 in to 28 ft Diameter in to ft				
Blank casing diameter 2 in. to 28 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 24 in., weight .70 lbs./ft. Wall thickness or gauge No154				
I TVDE OF CODEEN OD DEDEOD ATION MATEDIAI.				
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)				
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)				
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify)				
SCREE	N-PERFOI	RATED INTERVALS: From 28 ft. to 38 ft., From ft. to ft.	.	
	GRAVEL	PACK INTERVALS: From 20 ft. to 40 ft From ft. to ft	· :.	
		ATED INTERVALS: From 28 ft. to 38 ft., From ft. to ft. From ft. to ft., From ft. to ft. PACK INTERVALS: From 20 ft. to 40 ft., From ft. to ft. From ft. to ft., From ft. to ft.	i.	
6 GROUT MATERIAL: 1 Neat Cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug				
Grout Intervals: From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify				
2 Sewe		5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)		
	rtight sewer		-	
Direction FROM	1 from wel	? How many feet?		
0	6	Topsoil		
6	11	Clay, tan, hard		
11	24	Clay, dark gray, hard		
24 38	38 40	Sand and gravel, medium to fine, loose Clay, gray, green, hard		
30	70	Ciay, gray, groon, nard		
7 CONT	RACTOR	R'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugge	d	
under my jurisdiction and was completed on (mo/day/year) Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 67-06				
Under the business name of Clarke Well & Equipment, Inc. by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three				
copies to k	copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.			