	WA	TER WELL RE	ECORD Fo	rm WWC-5	KSA 82a-1	1212 [[O No. BS	3M2(S)			
1 LOCATION OF WATER WELL:	Fraction				ection Number	To	wnship Nu	mber	Ran	ge Numbe	er
County: Harvey	NW ½		/ -	,	8	T	23	S	R	2	W
Distance and direction from nearest tow 730 feet north of center of NW	n or city street	address of we 1725 feet e	ell if located v	vithin city? ter of Go	lden Prairie	9					
2 WATER WELL OWNER: City of		., 20 1001 0	401 01 0011		7.001111						
RR#, St. Address, Box # : 6016 S	outh Sprin	g Road				Boa	rd of Agricu	ulture. Divi	sion of Wa	ater Resc	urces
City, State, ZIP Code : Halste	ad, Kansas	67056					lication Nu				
2 LOCATE WELL'S LOCATON WITH	4				11 "				1400		
AN "X" IN SECTION BOX:	h	COMPLETE			11 ft. ELE [.] 17 4	VATION:					
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Depth(s) Grou WELL'S STAT			17	ft. below land	t. Z	neasured o	n mo/day/	30	5/27/200	ft. 06
↑ ^ 	t	mp test data:			it. Delow land				,. 		
NW NE			147-11					L			gpm
W E	Bore Hole Dia	meter 8	in. to	41		ft. and		in	. to		ft,
-	Bore Hole Dial WELL WATER 1 Domes 2 Irrigation	TO BE USE	DAS: 5 P	ublic water	supply	8 A	ir condition	าใก้ฐี 11	1 Injection	n well	
swse	1 Domes	stic 3 Feed	llot 6 0	il field wate	er supply arden (domesti	6	ewatering	12	2 Other (Specify be	elow)
	_			_		_	_		mo/day/y		
S	Was a chemic submitted	ai/bacteriolog	licai sampie s	ubmitee t			Disinfected				was
5 TYPE OF BLANK CASING USED:	Submitted	5 Wron	ight Iron	8 Con	crete tile						1
1_Steel 3 RMP(SR)		-		er (specify belo			Weld		O.apoo	
PVC 4 ABS	,	7 Fiber			(,			aded	X	
Blank casing diameter 2	in. to		Dia	ir	ı. to	ft., Di	а				ft.
Casing height above land surface	36	in., weight		0.68	bs./ft.	Wall thi	ckness or	gauge No.	- 5	3ch. 40	
TYPE OF SCREEN OR PERFORATION	MATERIAL:				7) PVC		10 Asbe	stos-ceme	nt		
1 Steel 3 Stainle 2 Brass 4 Galvar	ess steel nized steel	5 Fiber 6 Cond	-	3	B RMP (SR) B ABS			r (specify) : used (ope			
SCREEN OR PERFORATION OPENIN		6 Conc		: ed wrappe		8 Sa			11 None	e (open h	ole)
1 Continuous slot (3)	Mill slot			wrapped		9 Dri	illed holes				
1	Key punched	0.4		cut		10 Ot	her (speci	fy)			
SCREEN-PERFORATED INTERVALS:		31 	. ft. to	41	ft.	-rom		rt. ti	.0		π.
	From	28	ft. to		ft.	From		ft. t			ft.
GRAVEL PACK INTERVALS:	From							π. υ			
6 GROUT MATERIAL: 1 Neat of	From	2 Cement g	ft. to	(a)	entonite	From 4 Other		ft. t	.0		ft.
				_	to	ff	r t. From		ft to		ft.
What is the nearest source of possible of	contamination:		om		10 Lives			14 Aba			
1 Septic tank	4 Lateral line		7 Pit privy		11 Fuel			15 Oil	well/ Gas	well	
2 Sewer lines	5 Cess pool		8 Sewage	•	12 Ferti	lizer stor	age	16 Oth	ner (specit	fy below)	
3 Watertight sewer lines	6 Seepage p	oit	9 Feedyar	d	13 Insec		orage				
Direction from well? FROM TO CODE	HTU	OLOGIC LOC		FROM	How many	/ feet?	- DI I	IGGING IN	ITEDVAL		
TROM TO CODE	LITT	OLOGIC LOC		PROM	10	ļ	FLU	IGGING IN	TERVAL		

		1									
Se	e attached	iog									-
	<u> </u>										

7 CONTRACTOR'S OR LANDOWNER			water well wa	_							
completed on (mo/day/yr))5/2006 102			this record is t						
Water Well Contractor's License No.	[Christen	sen Com		Water Well R			on/(mo/	day(yr)	09/1/2/2	
under the business name of INSTRUCTIONS. Please fill in blank						by (signa nt of Heal		onment. Bu	read of W	ater, 1000	sw
Jackson St., Ste. 420, Topeka, Kansa											

TEST HOLE REPORT

LAYNE Western, a Div. of LAYNE Christensen Wichita, Kansas

Contract Name: Wichita ASR Test Hole No. BSM-02(\$)								
			Date:	August 26, 2006				
			Driller:	Carl Felton				
Location of Test Hole:		Elevation of Test Hole:						
			Static Water Level:					
Page 1			Measured	Hours After Completion				
			<u> </u>					
From	To	Description of Strata						
0	5	brown sandy silt, very fine						
5	10	orange sandy silt, very fine						
10	15	orange, brown sandy silty clay, low to medium plastic						
15	20	olive, orange silty clay, medium plastic, slight sand						
20	25	gray, olive silty clay, medium plastic, slight sand						
25	30	gray, olive silty clayey sand, fine to coarse, medium plastic						
30	35	gray, olive silty sand, fine to coarse, clay lens						
35	40	gray, olive silty sand, fine to coarse with gravel, clay lens						
40	45	red-orange, olive silty clay, low to medium plastic						