CORRECTED							
WATER WELL RE	CORD OB4S	Form W	WC-5	D	ivision of Wate	r Resources App. N	lo.
1 LOCATION OF WA		Fraction		Secti	on Number	Township No.	Range Number
County: Harvey		SW 1/4 SE 1/4 SE			29		
Street Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:		
from nearest town or intersection: If at owner's address, check here .					Latitude: .38* 00' 52.6" (in decimal degrees) Longitude: 097* 33' 56.5" (in decimal degrees)		
1/2 mile east of intersection SW 24th St. and 199th St. on the north					Elevation: (in decimal degrees)		
side of SW 24th St.					Datum: WGS 84, X NAD 83, NAD 27		
2 WATER WELL OWNER: City of Wichita				Colle	Collection Method:		
RR#, Street Address, Box #: 455 North Main Street					GPS unit (Make/Model: Garmin)		
City. State. ZIP Code : Wichita, KS 67202					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m		
3 LOCATE WELL							
WITH AN "X" IN	4 DEPTH OF	COMPLETED WEL	L .30		ft.		
WITH AN "X" IN SECTION BOX: A DEPTH OF COMPLETED WELL 30 ft.						(3) ft.	
, N	WELL'S STATIC WATER LEVEL!!!						lay/yr10/23/2009
NW NE	Described Disputed in to 40 A and in to 4						ıрıng gpm
W							Injection well
ew er	Domestic Feedlot Oil field water sunnly Devotering Other (Specify below)						
SW SE	☐ Irrigation	☐ Industrial ☐	Domestic-la	wn & ga	arden 🔲 Mo	onitoring well .O	bservation
	Was a chemical/	bacteriological sample	e submitted t	o Depar	tment?	Yes 🗹 No	
S		day/yr sample was sul					
1 mile		fected? Yes					
5 TYPE OF CASING	JSED: Stee	PVC 🗆			***************************************	••••	
CASING JOINTS:	Ø Mari	nped	K Threade	d			
Casing diameter .2	in. to 20	ft., Diameter	in.	to	ft., D	iameter	in. to ft.
Casing height above is	ind surface	weight		lbs./1	t., Wall thic	kness or gauge N	0!24
	TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot							
Louvered shutter							
From							
GRAVEL PACK INTERVALS: From						to ft.	
		From	ft. to		ft., From	ft.	to ft.
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other							
Grout Intervals: From	of possible seems	!	1	n. to	ft.,	rrom	tt. tott.
What is the nearest source of possible contamination: Septic tank						ner (snecify helow)	
Sewer lines	Ccsspool		Fuel storag		Abandoned		ici (specity ociow)
☐ Watertight sewer	ines Seepage p	it Feedyard	Fertilizer s	torage	Oil well/ga	s well	
Direction from well			, ,		ell . Over 10		
FROM TO	LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) or PLU	IGGING INTERVALS
Log at	tached						

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year)10/23/2009 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 755 This Water Well Record was completed on (moldands) 11/06/2009							
under the business name ofSargent Drilling							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						C [] N L C	
KSA 82a-1212				CI	icck. Uwn	ite Copy, 🔲 Bli	ue Copy, Pink Copy

Sargent Drilling

INDUSTRIAL ENGINEERING COMPLETE MUNICIPAL AND INDUSTRIAL WELL AND PUMP SERVICE

PO Box 367 Geneva, NE 68361-0367 846 South 13th St.

Phone: (402) 759-3902 1-888-496-3902

TEST HOLE LOG

CUSTOMER: City of Wichita				
WELL ID: OB4S				
LOCATION: SW 1/4 SE 1/4 SW 1/4, 29-T23S-R2W, Harvey Co., KS				
LATITUDE: 38° 00' 52.6"				
LONGITUDE: 097° 33' 56.5"				
FOOTAGES: 169 feet from the South section line and 2991 feet from the East section line.				
DATE: 10-23-09	DRILLED BY: CL			

SWL: PWL:

from feet - to fee	<u>et</u>
0 13	Topsoil and clay
13 30	Fine, medium and coarse sand and fine gravel
30 40	Clay

Well Depth: 30' Bore Hole Dia: 6"

Plain casing: 20' of 2" Perf. casing: 10' of 2"

Gravel pack from 17' to 30' Bentonite from 0' 10 17'

dh